



9 NOV 2017

ATIS 120.9 398	TWR 118.1 123.0	SMC 119.9	FIA (AH) ML CEN 135.7	CTAF (AH) 118.1	AWIS (AH) 120.9	Bearings are Magnetic Elevations in FEET AMSL
-------------------	--------------------	--------------	--------------------------	--------------------	--------------------	--



REFERENCE WAYPOINT MB NDB



10 NM MSA 3700

AD ELEV 55

SECTOR A

MISSED APPROACH:
TURN RIGHT, TRACK 158°. CLIMB TO 2200FT.

NM FM NDB	25	15	12	8	5	0													
CIRCLING MINIMA	A,B: 1000-2.4			C: 1010-4.0			D: N/A												
NM FM NDB	6.4	6	5	4	3	2.7	2.6												
ALT (3° APCH PATH)	2200	2070	1750	1430	1110	1010	1000												

SECTOR B

MISSED APPROACH:
TURN AS APPROPRIATE, TRACK 158°. CLIMB TO 2200FT.

NM FM NDB	20	15	11	8	5	0													
CIRCLING MINIMA	A,B: 1000-2.4			C: 1010-4.0			D: N/A												
NM FM NDB	8.7	8	7	6	5	4	3	2.7	2.6										
ALT (3° APCH PATH)	2900	2700	2390	2060	1750	1430	1110	1010	1000										

MONTY TO MB

MISSED APPROACH:
TURN LEFT, TRACK 158°. CLIMB TO 2200FT.

NM FM NDB	15	10	7	5	2	0													
CIRCLING MINIMA	A,B: 800-2.4			C: 1010-4.0			D: N/A												
NM FM NDB	5.5	5	4	3	2.1	1.4													
ALT (3° APCH PATH)	2100	1950	1630	1310	1010	800													

Changes: STEP ALT, Editorial.

MMBDG01-153