

ATIS 120.9 398	TWR 118.1 123.0	SMC 119.9	FIA (AH) ML CEN 135.7	CTAF (AH) 118.1	AWIS (AH) 120.9	Bearings are Magnetic Elevations in FEET AMSL
-------------------	--------------------	--------------	--------------------------	--------------------	--------------------	--

REFERENCE WAYPOINT MB NDB

25 NM MSA

3300 B-180°

4700

MB NDB 2200

B-085°

B-275°

10 NM MSA 3700

MB NDB 398

AD ELEV 55

TEMIS TO MB

NM FM NDB	25	19	15	9	7	5	1	0							
CIRCLING MINIMA	A,B: 1000-2.4			C: 1010-4.0			D: N/A								
NM FM NDB	13.3	12	11	10	9	8	7	6	5	4	3	2	1	0.7	0.6
ALT (3° APCH PATH)	5000	4600	4280	3960	3640	3330	3010	2690	2370	2050	1730	1420	1100	1010	1000

LTV TO MB

NM FM NDB	25	20	17	15	9	5	4	2	0						
CIRCLING MINIMA	A,B: 800-2.4			C: 1010-4.0			D: N/A								
NM FM NDB	12.5	12	11	10	9	8	7	6	5	4	3	2	1	0.7	0.3
ALT (3° APCH PATH)	4700	4550	4230	3910	3590	3270	2950	2640	2320	2000	1680	1360	1050	960	800