


STANDARD INSTRUMENT DEPARTURES (SID)
OAKLEY SIX DEPARTURE (RADAR)
OAKLEY, QLD (YBOK)

5 SEP 2024

ATIS 124.3 254	APP 125.4	ACD 133.35	TWR 120.1	SMC 121.9	FIA (AH) BN CEN 121.2	CTAF+AFRU (AH) 127.65	PAL 121.3	Bearings are Magnetic. Elevations in FEET AMSL
-------------------	--------------	---------------	--------------	--------------	--------------------------	--------------------------	--------------	---



OAKLEY SIX DEPARTURE (RADAR)

RWY 05

- GRAD 3.3%
- Track 044°
- At 2300FT, but not before DER, turn to assigned heading or track
- When directed contact Approach for radar vectors

RWY 09

- GRAD 3.6% to 2800FT, then 3.3% (5% to 2400FT)
- Track 089°
- At 2400FT, but not before DER, turn to assigned heading or track
- When directed contact Approach for radar vectors

RWY 14

- GRAD 4.1% to 2800FT, then 3.3% (5% to 2300FT)
- Track 135°
- At 2300FT, but not before DER, turn to assigned heading or track
- When directed contact Approach for radar vectors

RWY 32

- GRAD 3.3%
- Track 315°
- At 2400FT but not before DER, turn to assigned heading or track
- When directed contact Approach for radar vectors

COMMUNICATIONS FAILURE PROCEDURE

- On recognition of communication failure:
- Squawk 7600
 - Maintain last assigned vector for two minutes and, if necessary, climb to minimum safe altitude to maintain terrain clearance, then
 - Proceed in accordance with the latest ATC route clearance acknowledged.