

09 JUL 2026

TOWNSVILLE/TOWNSVILLE INTL, QLD (YBTL) Page 1

ATIS 114.1 133.5 276	ACD 128.1	SMC 121.8 264.6	TWR 118.3	FIA (AH) BN CEN 120.55	CTAF+AFRU (AH) AFRU+PAL (AH) 118.3	AWIS (AH) 133.5	Bearings are Magnetic Elevations in FEET AMSL
-------------------------	--------------	--------------------	--------------	------------------------------	--	--------------------	--

25 NM MSA

**DME USING TL DME
REFERENCE WAYPOINT TL VOR**

SPEED
MAX IAS 250KT
BELOW 10,000FT

TL ...
VOR/DME 114.1

TVL ...
NDB 276

* NO CIRCLING IN
SECTOR EAST OF
RWY 01 & RWY 19.

AD ELEV 18

SECTOR A

VOR or NDB

MISSED APPROACH:

TURN RIGHT,
TRACK 290°. CLIMB TO 4700ft OR AS DIRECTED BY ATC. MAX IAS 200KT.

NM TO TL VOR			25	15	13					7	5	0					
CIRCLING MINIMA			A,B: 1350-2.4			C: 1350-4.0			D: 1380-5.0								
NM TO TL VOR			13	12	11	10	9	8	7	6	5	4	3	2.5			
ALT (3° APCH PATH)			4700	4380	4060	3740	3420	3110	2790	2470	2150	1830	1510	1350			

SECTOR B

VOR or NDB

MISSED APPROACH:

TURN LEFT OR RIGHT,
AS REQUIRED TRACK 290°. CLIMB TO 4700ft OR AS DIRECTED BY ATC.

NM TO TL VOR			25	15	14					10	5	0					
CIRCLING MINIMA			A,B: 1410-2.4			C: 1410-4.0			D: 1410-5.0								
NM TO TL VOR			12.8	12	11	10	9	8	7	6	5	4	3	2	0.9		
ALT (3° APCH PATH)			5200	4930	4610	4290	3970	3650	3330	3020	2700	2380	2060	1750	1410		

SECTOR C

VOR or NDB

MISSED APPROACH:

TURN LEFT,
TRACK 290°. CLIMB TO 4700ft OR AS DIRECTED BY ATC.

NM TO TL VOR			25	16	13					6	0						
CIRCLING MINIMA			A,B: 2850-2.4			C: 2850-4.0			D: 2850-5.0								
NM TO TL VOR			10.4	10	9	8	7	6	5	4	3						
ALT (3° APCH PATH)			5200	5080	4770	4450	4130	3810	3490	3180	2850						

Changes: MINIMA, Editorial.

BTLDG01-187