

**STANDARD INSTRUMENT DEPARTURES (SID)
LAUNCESTON ONE DEPARTURE (RADAR) RWY 14R
LAUNCESTON, TAS (YMLT)**

30 NOV 2023



ATIS 112.6 (TWR HR) 134.75 (H24)	AWIS (AH) 112.6	TWR 118.7	LT APP/FIA (AH) ML CEN 123.8	CTAF+AFRU (AH) 118.7	AFRU+PAL (AH) 118.7	Bearings are Magnetic Elevations in FEET AMSL
--	--------------------	--------------	---------------------------------	-------------------------	------------------------	--

NOT TO SCALE



SPEED
• MAX IAS 250KT
BELOW 10,000ft

**CLASS D SPEED
LIMITS APPLY**



10 NM MSA 5800

LAUNCESTON ONE DEPARTURE (RADAR)

RWY 14R

- GRAD 4.6% to 6300ft, then 3.3%
- Track 133°
- AT or ABV 2000ft turn to assigned heading or track

COMMUNICATIONS FAILURE PROCEDURE

- On recognition of communications failure
- Squawk 7600
 - Maintain last assigned vector for two minutes and, if necessary, climb to minimum safe altitude to maintain terrain clearance, then
 - Proceed in accordance with the latest ATC route clearance acknowledged.

Changes: FROM SUP H40/23.

MLTDP09-177