

VOR-Y RWY 29
DARWIN, NT (YPDN)

ATIS 128.25 308 316.2	APP-E 125.2 APP-W 134.1	SMC 121.8	TWR 133.1	DEP 123.0	Bearings are Magnetic Elevations in FEET AMSL
------------------------------------	--	---------------------	---------------------	---------------------	--

CAUTION
VFR HELO OPS UP TO 500FT
AGL EAST OF 3NM STEP

12 20 00S

12 30 00S

130 50 00E

131 00 00E

12 20 00S

12 30 00S

130 50 00E

131 00 00E

Holding at DN VOR

TR IN TURN	TIME	MIN ALT	DME LMT
088° Right	1	3000	

10 NM MSA 3000

148

230

AD ELEV 103

[illegible]

1. MAX IAS:
INITIAL: CAT C/D 210KT
2. ACFT MAY BE RADAR
VECTORED TO FINAL.
- *3. NO CIRCLING IN SECTOR
SW OF RWY 11/29 AND
RWY 18/36 BEYOND 2.5NM.

CATEGORY	A	B	C	D
S-I VOR	1100 (1019-4.9)			
CIRCLING *	1100 (997-2.4)		1100 (997-4.0)	1100 (997-5.0)
ALTERNATE	(1497-4.4)		(1497-6.0)	(1497-7.0)

PDNVO02-186