

ILS-Z or LOC-Z RWY 03
PERTH, WA (YPPH)

CAUTION:
GP FALSE INDICATIONS
DUE ACFT LINING UP
FROM TWY C11

ATC APCH SPEEDS

NM	FM	THR	SPEED KT
BITUM			185 -160
5			160 -150

Holding as directed by ATC

TR	IN	TURN	TIME	MIN ALT	DME LMT

AD ELEV 67
Bearings are Magnetic
Elevations in FEET AMSL

NM TO IPN DME	9.2	9	8	7	6	5	4	3	2	1.4			
ALT (3° APCH PATH)	3000	2930	2610	2290	1970	1650	1340	1020	700	520			

MISSED APPROACH:
 TRACK 016°
 AT 1500ft TURN LEFT
 TRACK 300°
 CLIMB TO 3000ft OR
 AS DIRECTED BY ATC.

RDH 56ft
 THR 03 ELEV 67

NM TO IPN DME	10	8	5	0.7	0
NM TO THR 03		7.8	4.8	0.5	0

NOTES
 1. MAX IAS: 105 KTS

CATEGORY	A	B	C	D/D _L
S-I ILS SA CAT I #	RA 148 DA 217 (150) 450 RVR			
S-I ILS	270 (203) 0.8 550 RVR			
S-I LOC	520 (453-1.7)			
CIRCLING *	760 (693-2.4)		1440 (1373-4.0)	1440 (1373-5.0)
ALTERNATE *	(1193-4.4)		(1873-6.0)	(1873-7.0)

PPH103-187