

GNSS ARRIVAL PROCEDURES WYNYARD, TAS (YWYY) Page 1

19 MAR 2026

AWIS 133.35	FIA ML CEN 122.6	CTAF+AFRU 126.9	AFRU+PAL 126.9		Bearings are Magnetic Elevations in FEET AMSL
----------------	---------------------	--------------------	-------------------	--	--

25 NM MSA

3100

WYY NDB

B-079° B-264°

5600

REFERENCE WAYPOINT WYY NDB

WYY NDB 302

NO CIRCLING

10 NM MSA 3100

* NO CIRCLING SOUTH OF
RWY 09 / 27 & RWY 05 / 23.

AD ELEV 63

KII TO WYY

NDB

MISSED APPROACH:

TURN LEFT,
TRACK 070°. CLIMB TO 3100ft.

NM TO WYY NDB	KII	15	9	5	0										
CIRCLING MINIMA					A,B: 1180-2.4		C: 1270-4.0		D: N/A						
NM TO WYY NDB	8.4	8	7	6	5	4	3	2.7							
ALT (3° APCH PATH)	3000	2870	2550	2230	1910	1600	1270	1180							

IRSOM TO WYY

NDB

MISSED APPROACH:

TURN RIGHT,
TRACK 340°. CLIMB TO 3100ft.

NM TO WYY NDB	IRSOM	15	9	5	0										
CIRCLING MINIMA					A,B: 1210-2.4		C: 1270-4.0		D: N/A						
NM TO WYY NDB	10.5	10	9	8	7	6	5	4	3	2.8	2.7				
ALT (3° APCH PATH)	3700	3550	3230	2910	2590	2270	1960	1640	1320	1270	1210				

SECTOR A

NDB

MISSED APPROACH:

TURN LEFT,
TRACK 030°. CLIMB TO 3100ft.

NM TO WYY NDB	25	15	10	5	0										
CIRCLING MINIMA					A,B: 1180-2.4		C: 1270-4.0		D: N/A						
NM TO WYY NDB	8.4	8	7	6	5	4	3	2.7							
ALT (3° APCH PATH)	3000	2870	2550	2230	1910	1600	1270	1180							

Changes: KII TO WYY TR, SECTOR A TR, MSA BRG.

WYYDG01-186