BENDIGO AVFAX CODE 3021

FLFV 710



VIC UTC +10 YBDG
364421S 1441947E VAR 11 DEG E CERT
AD OPR City of Greater Bendigo, PO Box 733, Bendigo, VIC, 3552, Email:

AD OPH City of Greater Bendigo, PO Box 733, Bendigo, VIC, 3552. Email: airport@bendigo.vic.gov.au. PH 03 5434 6000. ARO 0499 700 128. Website: www.bendigoairport.com.au.

REMARKS

- 1. AD fees apply refer to website for details.
- This AD is a Security Controlled Airport. A valid ASIC must be displayed when airside.
- Australian standards approved hi-visibility clothing/vest to be worn whilst on APN, TWY and RWY.
 - PPR for all PRKG on RPT APN. CTC ARO mobile.

HANDLING SERVICES AND FACILITIES

Skyfuel: AVGAS and JET A1. H24 self-service bowsers accepts MC, V and Skyfuel Carnet card. PH 0418 862 100 or 0417 780 280. Refer to www.skyfuel.com.au for site information and orientation. IOR Aviation Pty Ltd: JET A1 by tanker. H24. \$130 call-out fee applies outside 0800 - 1700 Local. PH Justin 0428 179 873.

APRONS AND TAXIWAYS

Code C ACFT APN access via TWY D only. All other TWY 5,700KG MTOW.

AERODROME OBSTACLES

- Lit TWR 891FT AMSL 276 DEG MAG, 1,740M FM ARP.
- Building spire 940FT AMSL BRG 201 DEG MAG 2.82NM FM ARP. Infringes inner HZS by 104FT.
- Phone TWR 878FT AMSL BRG 222 DEG MAG 1.2NM FM ARP. Infringes inner HZS by 41FT.
- Transmission TWR:
 - a. 1,059FT AMSL BRG 187 DEG MAG 2.82NM FM ARP. Infringes COS by 92FT.
 - 1,086FT AMSL BRG 193 DEG MAG 3NM FM ARP. Infringes COS by 92FT.

METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT C, METAR/SPECI.
- AWIS PH 03 8470 3203 Report faults to BoM.
- AWIS FREQ 128.15 (requires one-second pulse to activate) Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

05/23 050 25a 5700/650 (94PSI) 130(427) W end grass. WID 18 RWS 60 17/35 171 52a PCN 21 /F /D /1400 (203PSI) /T WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 17/35 LIRL AFRU+PAL 119.3 SDBY PWR AVBL RWY 17/35 PAPI(1) AFRU+PAL 119.3 3.0 DEG50FT SDBY PWR AVBL

Left side only.

RWY 17/35 edge light spacing: 60M.

OTHER LIGHTING

- SDBY PWR switchover time: 15 SEC.
- 2. RWY guard lights (RGL) at RWY/TWY intersections.
- TWY LGT: Blue edge on D.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 126.8 Circuit area

LOCAL TRAFFIC REGULATIONS

- Circuit activity not permitted BTN 2200-0700 Local.
- 2. ACFT engine run up not permitted on RPT APN.
- All Code C ACFT must roll through and use RWY turning nodes and MAX radius turns on RWY and APN.
- ACFT advised to use tie-down near SkyFuel APN due to heavy prop wash from rotary ACFT.

FLIGHT PROCEDURES

Right hand CCTS RWY 05 and RWY 35.

CTAF - AFRU 119.3

ADDITIONAL INFORMATION

Wildlife hazard exists:

- a. Refer to NOTAM for seasonal INFO.
- b. Flying fox in VCY of AD particularly 30MIN FM last light.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3469, 3470.
- 2. Also refer to AIP Departure and Approach Procedures.