


FLINDERS ISLAND

ELEV 34

AVFAX CODE 7012

TAS
400529S
AD OPR Flinders Council, PO Box 40, Whitemark, Flinders Island, TAS, 7255. Email:
richard.harley@flinders.tas.gov.au: airport.operations@flinders.tas.gov.au. PH 03 6359 2144 (BH).
ARO H24 0429 813 929. Website: www.flinders.tas.gov.au.

1475934E
UTC +10
VAR 14 DEG E
YFLI
CERT



REMARKS

1. This AD is a Security Controlled Airport.

2. AD Charges apply, refer to website.

HANDLING SERVICES AND FACILITIES

AVGAS, JET A1. 24HR prior notice required CTC ARO. Overwing refuelling only. AH call-out fee may apply.

PASSENGER FACILITIES

HC/TX/AC/LG/RF/WC.

APRONS AND TAXIWAYS

TWY B MAX weight - 4,000KG.

SURFACE MOVEMENT GUIDANCE

RWY 32 fixed distance and TDZ markings displayed 20M to N.

AERODROME OBSTACLES

1. RWY 05 - Unlit fence 4.5FT ABV and 11M NE of RWS end.

2. RWY 32 - Unlit fence 5.3FT ABV and 11M NW of RWS end.

3. Group of trees BRG 051 DEG MAG 3,680M FM ARP. Infringes TKOF SFC by 14FT.

4. Lit OBST:

a. 399FT AMSL, BRG 087 MAG 2NM FM ARP.

b. 439FT AMSL, BRG 343 MAG 1.1NM FM ARP.

c. 499FT AMSL, BRG 310 MAG 2.5NM FM ARP.

d. 552FT AMSL, BRG 108 MAG 2.9NM FM ARP.

e. 653FT AMSL, BRG 342 MAG 1.7NM FM ARP.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.

2. AWIS PH 03 6283 8601 - Report faults to BoM.

3. AWIS FREQ 134.4 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

05/23 047 35c PCN 7/F/B/0.61 MPa/T Sealed WID 30 RWS 90

14/32 130 56c PCN 7/F/B/0.61 MPa/T Sealed WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 05/23 LIRL AFRU+PAL 127.8 SDBY PWR AVBL

RWY 14/32 LIRL AFRU+PAL 127.8 SDBY PWR AVBL

1. RWY edge light spacing: 05/23: 90M; 14/32: 90M.

2. RWY 23 and RWY 32: AFRU+PAL activation range may be reduced to the N due to high terrain.

OTHER LIGHTING

HBN	FLG 1 R	399FT AMSL BRG 087 MAG 2NM FM ARP.
HBN	FLG 1 R	552FT AMSL BRG 108 MAG 2.9NM FM ARP.
HBN	FLG 1 R	439FT AMSL BRG 343 MAG 1.1NM FM ARP.
HBN	FLG 1 R	653FT AMSL BRG 341 MAG 1.7NM FM ARP.
HBN	FLG 1 R	499FT AMSL BRG 310 MAG 2.5NM FM ARP.

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 126.5 Circuit area

LOCAL TRAFFIC REGULATIONS

1. VHF transmissions of taxiing ACFT are subject to ground shielding. Extreme caution must be exercised.
2. Parking restrictions:
 - a. Bay 1 scheduled Air Transport Operation (ATO) only.
 - b. Bay 2 shared with RFDS, Air Ambulance and other ATO - contact ARO.
 - c. Bay 3 AVBL for itinerant ACFT above 5,700KG - contact ARO.
 - d. Light ACFT to park on grass APN adjacent to main APN.
 - e. TWY B and grass APN for private hanger ACFT only - contact ARO.
 - f. Fuel bay parking not permitted unless ACFT requiring fuel - contact ARO.
3. All ACFT ABV 5,700KG must use RWY end turning node.

FLIGHT PROCEDURES

1. Right hand circuits RQ when OPR on RWY 05 and 14.
2. Night landings not permitted RWY 23. Night takeoffs not permitted RWY 05.

CTAF - AFRU 127.8

ADDITIONAL INFORMATION

Bird and wallaby hazard exists.

CHARTS RELATED TO THE AERODROME

1. WAC 3556.
 2. Also refer to AIP Departure and Approach Procedures.
-