FL EV 627

LONGREACH AVFAX CODE 4103

د	QLD 2326
248° 1.5NM	T AD C
Longreach	► Emai 0419
1936	REN
× · · •	1.
*	2.
Og A ^B	

DUTC +10 YLRE 2603S 1441649E VAR 7 DEG E CERT O OPR Longreach Airport Pty Ltd, PO Box 503, Longreach, QLD, 4730.

Email: info@Ireairport.com.au. PH Airport Manager 0428 780 246. ARO 0419 414 895. Website: www.longreachairport.com.au.

EMARKS

- AD Charges: All ACFT.
- This AD is a Security Controlled Airport. All pilots and operators required to possess and display a current Aviation Security Identification Card (ASIC) when airside, including all GA areas. Passengers are to be escorted at all times.
 RPT apron is a security restricted area. Access for non-RPT OPS
 - RPT apron is a security restricted area. Access for non-RPT OPS by permission from AD OPR only.

HANDLING SERVICES AND FACILITIES

AIR BP - Tim Rayner: 2130-0600 UTC MON-FRI, AH PN (call-out fee may apply). Phone: Office 07 4658 1520 or 0417 624 422. BP Cardswipe AVGAS bowser - Air BP card only. Payment can be made with cash, cheque or credit card by PRIOR arrangement with agent. AVGAS and JET A1.

General

The OPR does not provide ACFT marshalling services. All requests for ACFT marshalling should be directed to the airlines or a FBO (if applicable).

PASSENGER FACILITIES

TX/HC/LG/WC/AC/RF

APRONS AND TAXIWAYS

- 1. TWY A PCN 24/F/C/1200 (174 PSI). MAX 29M wingspan.
- 2. TWY B PCN 10/F/C/850 (123 PSI). MAX 29M wingspan and 10,000KG.
- 3. TWY C PCN 24/F/C/1200 (174 PSI). MAX 36M wingspan.
- 4. GA APN MAX 15M wingspan and 5,700KG.

AERODROME OBSTACLES

Multiple LIOL - Radio masts 1,306FT AMSL at 232321.42S 1441324.05E, painted and lit.

METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT C, METAR/SPECI.
- 2. AWIS Phone 07 3564 3723 Report faults to BoM.

PHYSICAL CHARACTERISTICS

04/22 039 64a PCN 24 /F /C /1200 (174PSI) /T Asphalt WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 04/22	LIRL	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 04/22	PAPI(1)	AFRU+PAL 126.7	3.0 DEG46FT	SDBY PWR AVBL
RWY 04/22	PTBL(2)			BY PRIOR
				ARRANGEMENT

- (1) Left side PAPI PAL HJ only.
- (2) EMERG only. 90MIN PN.

RWY edge light spacing: 60M.

OTHER LIGHTING

ABN FLG 8 W

1. TWY LGT: Blue edge on A and C.

2. SDBY PWR switchover time: 10SEC.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE

122.1 On Ground

RADIO NAVIGATION AND LANDING AIDS

NDB	LRE 353	232542.3S	1441720.9E	Range 120 (HN 85)	(1)
(1)	Pilot monitored				

LOCAL TRAFFIC REGULATIONS

Helicopters with skid landing gear not permitted on the RPT apron.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Bird hazard exists.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3234.
- 2. Also refer to AIP Departure and Approach Procedures.