
NORFOLK ISLAND AVFAX CODE 2402

OTHUTC +11YSNF290233S1675617EVAR 15 DEG ECERTAD OPR Norfolk Island Regional Council, PO Box 149, Norfolk Island, NSW, 2899. Email:info@airport.gov.nf. PH Primary +6723 22445: Secondary: +6723 23666. Fax +6723 23201.



REMARKS

- 1. This AD is a Security Controlled Airport.
- All non air transport operational ACFT must obtain prior approval from the Airport Manager, Norfolk Island AD. 24HR PN required.
- 3. Local OPR MNM 60MIN advice of intention to OPR. YSNF.
- 4. ACFT movement and parking fees apply. See council fees and charges schedule.

HANDLING SERVICES AND FACILITIES

Fuel: Burnt Pine Fuel - Phone BH/Fax +6723 24122, Mobile +6723 50498 or +6723 56750, Company FREQ 131.9. Limited stocks, confirm availability before DEP for Norfolk Island. AVGAS, JET A1. VISA, MC and Cash only.

Ground Handling: Burnt Pine Travel Airport Services - Phone BH +6723 22196.

Mobile +6723 50190 or +6723 56643, Company FREQ 131.9.

RESCUE AND FIREFIGHTING SERVICES

CAT 6 - CTC +6723 22049:

- a. 2000 0600 UTC MON and TUE
- b. 2230 0230 UTC THU
- c. 2000 0630 UTC FRI
- d. 2000 0500 UTC SAT
- e. 0130 0430 UTC SUN

Note: Service provided on WED upon request.

SURFACE MOVEMENT GUIDANCE

THR - green; RWY ends - red; pavement ends - blue.

AERODROME OBSTACLES

- 1. AD HBN and ABN located on Mount Pitt, situated 344DEG/1.4NM from AD (ELEV 1,065FT AMSL).
- 2. Secondary LIT WDI 345FT AMSL BRG 99 MAG 713M FM ARP. Infringes TNS.
- 3. Secondary LIT WDI 393FT AMSL BRG 304 MAG 1,008M FM ARP. Infringes TNS.

METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT A, METAR/SPECI, AD WRNG.
- 2. AWIS Phone 02 9353 6443 Report faults to BoM.

PHYSICAL CHARACTERISTICS

04/22	035	47a	PCN 12 /F /C /580 (84PSI) /U	WID 30	RWS 90					
11/29	107	64a	PCN 49 /F /B /1410 (205PSI) /T Grooved	WID 45	RWS 150					
Both side of RWY 04/22 TNS infringed.										

AERODROME AND APPROACH LIGHTING

	RWY 0	-			ING						
	RWY 0		PTBL(2)				SDBY PWR AVB BY PRIOR	L			
		4/22	TTDE(Z)				ARRANGEMENT	-			
1	RWY 0	4	PAPI(1)		3.0 DEG	50FT	SDBY PWR AVB				
l	RWY 0	4	RTIL				SDBY PWR AVB	L			
	RWY 1		MIRL				SDBY PWR AVB				
	RWY 1		PAPI		3.0 DEG5	50FT	SDBY PWR AVB	L			
	RWY 1	1/29	PTBL(2)				BY PRIOR	-			
	RWY 1	1/20	BTIL				ARRANGEMENT SDBY PWR AVB				
	(1)		ide only				SUDI FWH AVD	L			
	(2)		G only. 90MIN P	N.							
			t spacing: 11/29		OM.						
(OTHE	R LIGH	ITING								
	ABN		ALTN 8 WG		Pitt (ELEV 1065	FT AMSL) 3	44DEG/1.4NM from	m			
				ARP.				.			
	HBN		OCC R	MIOL - Lo 1.4NM froi		(ELEV 1065	SFT AMSL) 344DE	G/			
	1.	Second	dary PWR switcl								
	2.		GT: Blue edge.								
	ATS A		0	OMMUNICAT	ION FACILITIE	s					
	FIS		CKLAND SP6			8867 13261	17904				
		WI	SELCAL								
1	JNICO	-	RFOLK ISLAN)	118.1 (1)						
	(a)	-									
	(1)		orfolk UNICOM".								
			GATION AND					(0)			
	DME NDB	NF NF	112.4/ 71X 260	290250.8S 290026.1S		OW 70 (C		(2)			
	VOR	NF	112.4	290250.4S		000 70 (0	7vv i iin70)	(3) (1)			
	(1)		onitored	200200.10	1070000.02			(•)			
	2)	Antenna ELEV 330FT - Pilot monitored									
((3)	144/2.3 to ARP - Pilot monitored									
l	LOCA	L TRA	FFIC REGUL	ATIONS							
	1.	All ACFT must use RWY end turning nodes. Any backtracking turns made prior to the RWY									
			ning nodes mov	anaaiintar faaa	due CEC demos						

- end turning nodes may encounter fees due SFC damage.
- Operators of jet ACFT are requested to use MNM power when turning or taxiing on apron and MAX radius turn on exiting PRKG bays.
- 3. RWY 04/22 OPS restricted to ACFT 5,700KG or BLW with the FLW exceptions.
 - a. ACFT up to and including DH8C may use RWY 04/22 if RWY 11/29 is operationally unsuitable; and
 - b. The section of RWY 04/22 BTN the apron exit and the intersection of the RWY is AVBL as a TWY by all ACFT using RWY 11/29.

FLIGHT PROCEDURES

- 1. Pilots are reminded that NZ altimetry setting PROC are applicable when OPR into and out of Norfolk Island.
- NZ regulations require aircraft flying within the Auckland Oceanic FIR to maintain vertical position with reference to standard pressure 1,013 HPA, with the exception that within proximity to the Norfolk Island AD aircraft must maintain altitude with reference to aerodrome QNH.
- Right hand CCTS RQ when OPR on RWY 04 and 11 due to Mount Pitt, located 344DEG/ 1.4NM from AD (ELEV 1,065FT AMSL).

CTAF 118.1

ADDITIONAL INFORMATION

- 1. Significant bird hazard at Philip Island (160DEG/5NM from AD, ELEV 913FT AMSL), and Nepean Island (131DEG/2.5NM from AD, ELEV 108FT AMSL).
- 2. Briefing services and flight information AVBL through Briefing Office on Phone 02 6268 5062 or Fax 02 6268 5033.
- Weather balloon launch APRX 0515, 1115, 2315 UTC FM 480M NE ARP. Launches may occur at other times.
- 4. SARWATCH: The responsibility of SAR for ACFT movements at Norfolk Island belongs with New Zealand.
- 5. Actual weather conditions can change rapidly and vary from forecasts.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3359.
- 2. Aerodrome Obstruction Chart Type A: RWY11/29, 1st Edition (April 2021).
- 3. Also refer to AIP Departure and Approach Procedures.