

**TROPICANA****ELEV 1104****AVFAX CODE 6403**

WA

UTC +8

YTRA


291112S

1243301E

VAR 2 DEG E

CERT

AD OPR Anglogold Ashanti Australia Ltd - GPO Box B91, Perth, WA, 6838. PH 08 9265 2000: AD Manager 08 9265 2300, 08 9265 2345. ARO 08 9265 2321, 0409 310 718.

**REMARKS**

1. Restricted OPS. PPR from AD OPR.
2. PRI source of PWR is derived from a generator.

**HANDLING SERVICES AND FACILITIES**

JET A1 private installation. AVBL to routine, scheduled and emergency service flights only.

**APRONS AND TAXIWAYS**

TWY A: PCN 25, sealed, WID 15M.

**AERODROME OBSTACLES**

1. Lit mast 1,464FT BRG 230DEG 4,414M FM ARP.
2. Lit weather station tower 33FT AGL PSN 291113.00S 1243301.00E 105M south of RWY centre line infringes transitional SFC.

**METEOROLOGICAL INFORMATION PROVIDED**

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 08 6216 2639 - Report faults to BoM.
3. AWIS FREQ 133.0 - (requires three one-second pulses to activate) - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

09/27 087 69a PCN 25 /F /A /1000 (145PSI) /U

WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

RWY 09/27 LIRL AFRU+PAL 126.7  
 RWY 09/27 PAPI(1) AFRU+PAL 126.7 3.0 DEG41.3FT  
 RWY 09/27 PTBL(2)

SDBY PWR AVBL  
 SDBY PWR AVBL  
 BY PRIOR  
 ARRANGEMENT

- (1) Left side.
  - (2) EMERG only. 90MIN PN.
- RWY edge light spacing: 09/27: 60M.

**OTHER LIGHTING**

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA MELBOURNE CENTRE 125.75

**LOCAL TRAFFIC REGULATIONS**

1. All ACFT ABV 5,700KG must use turning nodes for 180DEG turns.
2. All ACFT to make MAX RAD turns at MNM speed to avoid SFC damage.
3. APN Bay 3 not AVBL HN.

**FLIGHT PROCEDURES**

Right hand CCTS RWY 27.

**CTAF - AFRU** 126.7

**ADDITIONAL INFORMATION**

Potential blasting at 1300 or 1800 WST at mine site 3.8NM south of AD.

**CHARTS RELATED TO THE AERODROME**

1. WAC 3352.
  2. Also refer to AIP Departure and Approach Procedures.
-