

OAKEY

| RWY | (CN) | TORA | TODA | ASDA | LDA |
|------------|-------------|---|---------------------|-------------|-------------|
| 05 | (MIL) | 914 (2999) | 974 (3195) (2.42%) | 914 (2999) | 914 (2999) |
| 23 | (MIL) | 914 (2999) | 974 (3195) (1.36%) | 914 (2999) | 914 (2999) |
| | | 1. TKOF/Climb SFC overall length 2,500M. | | | |
| | | 2. TKOF/Climb SFC inner edge WID 80M. | | | |
| | | Slope 0.19% down to SW. RWY WID 23 RWS WID 90 | | | |
| 09 | (MIL) | 1089 (3573) | 1149 (3770) (1.8%) | 1089 (3573) | 1089 (3573) |
| 27 | (MIL) | 1089 (3573) | 1149 (3770) (2.45%) | 1089 (3573) | 1089 (3573) |
| | | 1. TKOF/Climb SFC overall length 2,500M. | | | |
| | | 2. TKOF/Climb SFC inner edge WID 80M. | | | |
| | | Slope 0.26% down to W. RWY WID 23 RWS WID 90 | | | |
| 14 | (MIL) | 1649 (5410) | 1709 (5607) (2.97%) | 1649 (5410) | 1649 (5410) |
| | | 1. RWY 14 2% SUPP GRAD - 1637(5370) | | | |
| | | 2. RWY 14 5400 FT (H24). | | | |
| 32 | (MIL) | 1707 (5600) | 1767 (5797) (1.35%) | 1707 (5600) | 1707 (5600) |
| | | 1. RWY 32 reduced to 5,400FT (HN). | | | |
| | | 2. TKOF/Climb SFC inner edge WID 180. | | | |
| | | 3. Extra pavement 58M included in AVBL RWY 32 TORA. | | | |
| | | 4. TKOF/climb SFC overall length 15,000M. | | | |
| | | Slope 0.02% down to NW. RWY WID 30 RWS WID 90 | | | |

SUPPLEMENTARY TAKEOFF DISTANCES

| | | | | |
|--------|-----------------|-----------------|-----------------|-----------------|
| RWY05- | 802(2631)(1.9) | 844(2769)(2.0) | 915(3002)(2.2) | |
| RWY09- | 1131(3711)(1.6) | | | |
| RWY27- | 944(3097)(1.9) | 988(3241)(2.0) | 1065(3494)(2.2) | |
| RWY14- | 1212(3976)(1.9) | 1633(5358)(2.0) | 1654(5426)(2.2) | 1680(5512)(2.5) |