

**AIP SUPPLEMENT
(SUP)****AIRAC****H71/22****Effective: 202208101600 UTC**

AERONAUTICAL INFORMATION SERVICE,
AIRSERVICES AUSTRALIA, GPO BOX 367,
CANBERRA ACT 2601

For **DISTRIBUTION** queries, contact:
Email: aim_editorial@airservicesaustralia.com

For **CONTENT** queries regarding this SUP, contact:
Email: nmitchell@capmet.com.au

KARLAWINDA MINE AIRPORT(YKWA), WESTERN AUSTRALIA - ERSA AND RDS INFORMATION

1. INTRODUCTION

- 1.1 This SUP publishes En Route Supplement Australia (ERSA) and Runway Distance Supplement (RDS) information for Karlawinda Mine (YKWA).

2. IMPLEMENTATION

- 2.1 The information published in the Appendices will become effective 202208101600 UTC, the certification status and any aerodrome operational limitations will be advised by NOTAM.

3. MORE INFORMATION

- 3.1 For more information about this aerodrome contact the ADO via the contact details published in Appendix 1.

4. CANCELLATION

- 4.1 This SUP will be cancelled when incorporated into the ERSA and RDS.

5. DISTRIBUTION

- 5.1 Airservices Australia website only.

Appendices

1. Karlawinda Mine (YKWA) - ERSA FAC
2. Karlawinda Mine - RDS

1. Karlawinda Mine (YKWA) - ERSA FAC

KARLAWINDA MINE

ELEV 1928

AVFAX CODE 6840

WA UTC +8 YKWA
234652S 1200806E VAR 1 DEG E TBA

AD OPR: Greenmount Resources Pty Ltd, Level 1, 28 Ord Street, West Perth, WA, 6005. PH: 08 9212 4600. Fax: 08 9212 4699.

Website: www.capmetals.com.au. Email: nmitchell@capmet.com.au.

AD MGR PH: 0423 141 604 (H24).

REMARKS

1. PPR.
2. HJ only.

HANDLING SERVICES AND FACILITIES

Marshalling, parking allocation and ground handling services by prior arrangement with AD MGR.

PHYSICAL CHARACTERISTICS

01/19	007	66a	PCN 28/F/A/1100 (160PSI) /T	WID 30M	RWS 280M
-------	-----	-----	-----------------------------	------------	-------------

AERODROME AND APPROACH LIGHTING

RWY 01/19 PTBL (1)

(1) EMERG only. 90MIN PN.

ATS COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 123.4

LOCAL TRAFFIC REGULATIONS

1. All fixed wing ACFT ABV 5,700KG must make MAX RAD turns at MNM speed at turn pads to avoid SFC damage.
2. All ACFT to follow APN markings.
3. All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi.
4. RWS not available for flight operations.

CTAF 122.0

ADDITIONAL INFORMATION

1. Blasting at 0500 UTC on intermittent days - MAG BRG 293 DEG 2.43NM FM ARP. CTC Blast Controller 0433 050 874.
2. Caution: Newman (YNWN) AD 28NM to NW. YNWN PROCS overlay and ADJ to PROCS at YKWA.

CHARTS RELATED TO THE AERODROME

1. WAC 3230.
2. Also refer to AIP Departure and Approach Procedures.

2. Karlawinda Mine RDS

RWY	CN	TORA	TODA	ASDA	LDA
01	3	2000 (6562)	2060 (6758)(2.42%)	2000 (6562)	2000 (6562)
19	3	2000 (6562)	2060 (6758)(2.16%)	2000 (6562)	2000 (6562)

Slope 0.25% down to S. RWY WID 30 RWS 280 Graded 90.

SUPPLEMENTARY TAKEOFF DISTANCES

RWY01-	1890 (6201) (1.6)	1967 (6453) (1.9)	2025 (6644) (2.2)
RWY19-	1931 (6335) (1.6)	2011 (6598) (1.9)	