

NDB RWY 03
BUSSELTON, WA (YBLN)

AWIS 128.05	FIA ML CEN 124.9	CTAF + AFRU 127.0	PAL 119.6		Bearings are Magnetic Elevations in FEET AMSL										
					Holding at NDB 										
					<table border="1"> <tr> <th>TR</th> <th>INTURN</th> <th>TIME</th> <th>MIN ALT</th> <th>DME LMT</th> </tr> <tr> <td>176°</td> <td>Left</td> <td>1</td> <td>2400</td> <td></td> </tr> </table>	TR	INTURN	TIME	MIN ALT	DME LMT	176°	Left	1	2400	
TR	INTURN	TIME	MIN ALT	DME LMT											
176°	Left	1	2400												
					AD ELEV 56										

[illegible]

1. MAX IAS : INITIAL
CAT A/B : 140KTS
CAT C/D : 210KTS
- *2. CAT A/B 1700FT
UNTIL ESTABLISHED
INBOUND
- #3. CIRCLING VALUES
ONLY APPLY TO
THIS PROCEDURE

CATEGORY	A	B	C	D
S-I NDB	1090 (1034 - 5.0)			
CIRCLING [#]	1090 (1034 - 2.4)	1090 (1034 - 4.0)	1150 (1094 - 5.0)	
ALTERNATE	(1534 - 4.4)	(1534 - 6.0)	(1594 - 7.0)	

BLNNB01-166