

RNP Z RWY 28
BROOME/INTL, WA (YBRM)

ATIS 128.2 **AWIS (AH)** 126.55 **TWR (CTAF+AFRU AH)** 126.0 **SMC (TWR HR)** 121.7 **FIA (AH)** 123.95 **AFRU+PAL** 126.0

RNP APCH
LNAV/VNAV RQMNTS:
 • YBRM QNH RQ
 • YBRM TEMP RQ
 • PROC TEMP RANGE +5°C TO +61°C

Holding at BRMEB

TR IN	TURN	TIME	MIN ALT	DME LMT
284°	Right	1	3000	

AD ELEV 57
 Bearings are Magnetic
 Elevations in FEET AMSL

Chart details include: 25 NM MSA (2100), 10 NM MSA 1500, YBRM ARP, 213, 344, 295, 390, 128, 223, 284°, 214°, 354°, 104°, 034°, 18 00 00S, 17 50 00S, 122 20 00E, 122 30 00E, 122 10 00E, 18 00 00S, 18 10 00S, Scale 1:500,000, 0 5NM.

NM TO NEXT WPT	BRMEM	0.8	1.4	2	3	4	BRMEF	1	2	3	4		
ALT (3° APCH PATH)		410	600	780	1100	1420	1740	2060	2370	2690	3000		

TRACK DCT TO BRMEH,
THEN TRACK 284°
CLIMB TO 2100FT.

MAF
BRMEH

MAPt
BRMEM

FAF
BRMEF

IF
BRMEI

IAF

284°

284°

284°

3°

1740

1500

3000

3000

BRMEA
BRMEB
BRMEC

TCH 50FT
THR 28 ELEV 23

MAPt

MDA

NM TO BRMEM

0.2

CATEGORY	A	B	C	D
LNAV/VNAV	410 (387-2.2)			
LNAV	600 (577-3.3)			
CIRCLING	650 (593-2.4)	840 (783-4.0)		850 (793-5.0)
ALTERNATE	(1093-4.4)	(1283-6.0)		(1293-7.0)

1. MAX IAS:
INITIAL : 210KT.
2. HOLDING NOT
CONTAINED IN
CTA

BRMGN02-172