

09 JUL 2026

ATIS 114.1 133.5 276	ACD 128.1	SMC 121.8 264.6	TWR 118.3	FIA (AH) BN CEN 120.55	CTAF+AFRU (AH) AFRU+PAL (AH) 118.3	AWIS (AH) 133.5	Bearings are Magnetic Elevations in FEET AMSL
-------------------------	--------------	--------------------	--------------	------------------------------	--	--------------------	--

**DME USING TL DME
REFERENCE WAYPOINT TL VOR**

SPEED
MAX IAS 250KT
BELOW 10,000FT

AD ELEV 18

SECTOR A

MISSED APPROACH:
TURN RIGHT,
TRACK 290°.
CLIMB TO 4700ft OR
AS DIRECTED BY ATC.
MAX IAS 200KT.

NM TO TL VOR	25	15	13	7	5	0								
CIRCLING MINIMA	A,B: 1350-2.4			C: 1350-4.0		D: 1380-5.0								
NM TO TL VOR	13	12	11	10	9	8	7	6	5	4	3	2.5		
ALT (3° APCH PATH)	4700	4380	4060	3740	3420	3110	2790	2470	2150	1830	1510	1350		

SECTOR B

MISSED APPROACH:
TURN LEFT OR RIGHT,
AS REQUIRED
TRACK 290°.
CLIMB TO 4700ft OR
AS DIRECTED BY ATC.

NM TO TL VOR	25	15	14	10	5	0								
CIRCLING MINIMA	A,B: 1410-2.4			C: 1410-4.0		D: 1410-5.0								
NM TO TL VOR	12.8	12	11	10	9	8	7	6	5	4	3	2	0.9	
ALT (3° APCH PATH)	5200	4930	4610	4290	3970	3650	3330	3020	2700	2380	2060	1750	1410	

SECTOR C

MISSED APPROACH:
TURN LEFT,
TRACK 290°.
CLIMB TO 4700ft OR
AS DIRECTED BY ATC.

NM TO TL VOR	25	16	13	6	0									
CIRCLING MINIMA	A,B: 2850-2.4			C: 2850-4.0		D: 2850-5.0								
NM TO TL VOR	10.4	10	9	8	7	6	5	4	3					
ALT (3° APCH PATH)	5200	5080	4770	4450	4130	3810	3490	3180	2850					

Changes: MINIMA, Editorial.

BTLDG01-187