

USE QNH RNP Z RWY 01
TOWNSVILLE/TOWNSVILLE INTL, QLD (YBTL)

ATIS 114.1 133.5 276
APP/DEP 126.8
TWR 118.3
SMC 121.8 264.6
FIA (AH) BN CEN 120.55
CTAF+AFRU (AH) AFRU+PAL (AH) 118.3
AWIS (AH) 133.5

RNP APCH
 LNAV/VNAV RQMNTS:
 • YBTL QNH RQ
 • YBTL TEMP RQ
 • PROC TEMP RANGE 0°C TO +61°C

Holding at PARPO

TR IN	TURN	TIME	MIN ALT	DME LMT
286°	Left	1	5200	

AD ELEV 18
 Bearings are Magnetic
 Elevations in FEET AMSL

NM TO NEXT WPT	GOTSI	4	3	2	1	TL2SF	5	4	3	2.9	2.3	RW01
ALT (3° APCH PATH)	3600	3410	3090	2770	2460	2140	1660	1340	1020	980	810	

MISSED APPROACH:
 TRACK DCT TO TL2SH;
 TURN RIGHT;
 TRACK 095°;
 CLIMB TO 3000FT OR
 AS DIRECTED BY ATC.

TCH 50FT
THR 01 ELEV 18

1. MAX IAS:
INITIAL : 200KT.
MAP TURN: 190KT.
- * 2. NO CIRCLING IN
SECTOR EAST OF
RWY 01 & RWY 19.
3. WHEN R752 ACT ATC
RADAR RQ AND APCH
VIA KAKRO NOT AVBL.
4. **COLOUR:** SEE
SPEC NOTICES.

CATEGORY	A	B	C	D
LNAV/VNAV	810 (792-4.2)			
LNAV	980 (962-5.0)			
CIRCLING *	1090 (1072-2.4)	1350 (1332-4.0)		1350 (1332-5.0)
ALTERNATE	(1572-4.4)	(1832-6.0)		(1832-7.0)

BTLGN05-177