



TOWNSVILLE/TOWNSVILLE INTL, QLD (YBTL)

ATIS			ACD	SMC		TWR	APP/DEP	FIA (AH) BN CEN	CTAF+AFRU (AH) AFRU+PAL (AH)	AWIS (AH)	Bearings are Magnetic Elevations in FEET AMSL
114.1	133.5	276	128.1	121.8	264.6	118.3	126.8	120.55	118.3	133.5	

A diagram showing a vertical line and a line labeled 'E' at a 7-degree angle from the vertical.

RNP 1



VOMPA TWO ARRIVAL

- **Cross** VOMPA AT or ABV 10,000ft
- From VOMPA track 343° to BEBUD
- **Cross** BEBUD AT or ABV 6000ft
- Track 343° to GUGAN
- **Cross** GUGAN BETWEEN 5200-6000ft
- From GUGAN track via RNP P RWY 01 (AR)

- From VOMPA track 007° to OLNUT
Cross OLNUT AT or ABV FL140
- Track 007° to LAPES
Cross LAPES AT or ABV 6000ft
- Track 007° to RURTO
- Track 007° to VILUN
- From VILUN track via RNP P RWY19 (AR)

- Squawk 7600, comply with vertical navigation requirements, but not below MSA.
- Track via the latest STAR clearance to the nominated runway, then fly the most suitable approach in accordance with ERSA EMERG Section 1.5.

BTLSR08-178