

RNP RWY 04
COOBER PEDY, SA (YCBP)

AWIS 122.125 **FIA ML CEN 120.7** **CTAF+AFRU 126.7** **PAL+AA 119.6**

134 30 00E 134 40 00E 134 50 00E

29 00 00S

774

742

BP2SJ 134° 4NM BP2SF 044° 3NM BP2SG 044° 4NM BP2SE 334° 4NM

RW04 3NM 3NM

898 927 910 1109 1117

774

758

29 10 00S

25 NM MSA

2200

YCBP ARP

R222H UNL SFC NOTAM

R246B UNLIM SFC NOTAM

134 40 00E 134 50 00E

0 Scale 1:500,000 5NM


Holding at BP2SJ

024° 204° 314°

TR IN	TURN	TIME	MIN ALT	DME LMT
134°	Left	1	2200	

AD ELEV 745

Bearings are Magnetic
Elevations in FEET AMSL

[illegible]

CATEGORY	A	B	C	D
LNAV/VNAV	1080 (346-1.9)			NOT APPLICABLE
LNAV	1270 (536-3.0)			
CIRCLING	1390 (645-2.4)	1620 (875-4.0)		
ALTERNATE	(1145-4.4)	(1375-6.0)		

1. MAX IAS:
INITIAL : 180KT.
2. PROC NOT AVBL
WHEN **R246B** ACTIVE.

CBPGN01-186