

RNP RWY 10  
**ELIWANA, WA (YEWA)**

**AWIS 122.275**      **FIA ML CEN 125.7**      **CTAF+AFRU 126.7**      **PAL+AA 119.6**      **UNICOM 126.7**

**RNP APCH LNAV/VNAV RQMNTS:**

- YEWA QNH and TEMP RQ
- PROC TEMP RANGE 0°C to +60°C

**Holding at EW2WD**

| TR IN | TURN  | TIME | MIN ALT | DME LMT |
|-------|-------|------|---------|---------|
| 099°  | Right | 1    | 4900    |         |

**AD ELEV 1576**  
Bearings are Magnetic  
Elevations in FEET AMSL

The chart displays a series of waypoints and their associated bearings and distances:

- EW2WD to EW2WE: 169°, 5NM
- EW2WE to EW2WI: 099°, 5NM
- EW2WI to EW2WF: 099°, 5.3NM
- EW2WF to CAMP: 099°, 2.5NM
- CAMP to RW10: 099°, 4NM
- RW10 to EW2WH: 077°, 4NM

The chart also includes a 25 NM MSA (4900) and a 10 NM MSA (4500). The airport is located at 1576 feet elevation. The chart is titled "YEWA ARP" and includes a note about the airport's elevation and bearing system.

| EW2WI | 4    | 3    | 2    | 1    | EW2WF | 4    | 3    | 2    | 1.8  | 1.2  | RW10 | NM TO NEXT WPT       |
|-------|------|------|------|------|-------|------|------|------|------|------|------|----------------------|
| 4900  | 4570 | 4250 | 3940 | 3620 | 3300  | 2890 | 2570 | 2250 | 2190 | 2000 |      | ALT ( 3° APCH PATH ) |

**MISSED APPROACH:**  
TRACK DCT TO EW2WH,  
THEN TURN LEFT,  
TRACK 077°. CLIMB TO 4900FT.

The profile view diagram illustrates the vertical profile of the approach path. The horizontal axis represents distance in nautical miles (NM) from the start of the approach (NM to RW10) to the runway threshold (THR 10 ELEV 1567). The vertical axis represents altitude in feet. The path begins at 4900 feet at 15.3 NM from RW10. It remains level until 10.3 NM, where it descends at a 3-degree angle. At 5.3 NM, the altitude is 2500 feet. At 2.5 NM, the altitude is 2400 feet. At 0 NM (RW10), the altitude is 2000 feet. The path continues to descend to 1567 feet at the runway threshold. A missed approach procedure is shown as a dashed line starting from the runway threshold, turning left to track 077 degrees, and climbing to 4900 feet.

| Distance (NM) | Altitude (Feet) | Point / Feature |
|---------------|-----------------|-----------------|
| 15.3          | 4900            | IAF             |
| 10.3          | 3400            | IF EW2WI        |
| 5.3           | 2500            | FAF EW2WF       |
| 2.5           | 2400            | MDA             |
| 0             | 2000            | MAPt RW10       |
| 4.0           | -               | MAHF EW2WH      |
| 0             | 1567            | THR 10 ELEV     |

1. MAX IAS :  
INITIAL: 210KT
- \*2. NO CIRCLING S  
OF RWY 10/28
3. COLOUR: SEE SPEC  
NOTICES
4. CAUTION: YBGD  
PROCS ADJACENT  
TO S

| CATEGORY  | A              | B               | C | D              |
|-----------|----------------|-----------------|---|----------------|
| LNAV/VNAV | 2000 (432-2.4) |                 |   |                |
| LNAV      | 2190 (622-3.5) |                 |   |                |
| *CIRCLING | 2440 (864-2.4) | 2680 (1104-4.0) |   | NOT AUTHORISED |
| ALTERNATE | (1364-4.4)     | (1604-6.0)      |   | NOT APPLICABLE |

EWAGN01-177