

RNP RWY 28
ELIWANA, WA (YEWA)

AWIS 122.275 **FIA ML CEN 125.7** **CTAF+AFRU 126.7** **PAL+AA 119.6** **UNICOM 126.7**

RNP APCH RNAV/VNAV RQMNTS:

- YEWA QNH and TEMP RQ
- PROC TEMP RANGE 0°C to +60°C

Holding at EW2EA

130°
029°
319°

TR IN	TURN	TIME	MIN ALT	DME LMT
209°	Right	1	4900	

AD ELEV 1576
Bearings are Magnetic
Elevations in FEET AMSL

NM TO NEXT WPT	EW2EM	0.3	1.0	2	3	4	5	6	EW2EF	1	2	2.2
ALT (3° APCH PATH)		2060	2260	2590	2900	3220	3540	3860	4200	4520	4840	4900

MISSED APPROACH:
 TRACK DCT TO EW2EH,
 THEN TRACK 274°.
 CLIMB TO 4900FT

MAHF EW2EH MAPt EW2EM FAF EW2EF IF/IAF EW2EI IAF

4.0 1.0 0 2.6 7.1 12.1 17.1 NM TO FW2FO

274° 2770 274° 4200 3° 274° 4900

TCH 50FT
THR 28 ELEV 1572

2770 2800 3400 EW2EA
EW2EB

1. MAX IAS :
INITIAL: 210KT
- *2. NO CIRCLING S
OF RWY 10/28
3. COLOUR: SEE SPEC
NOTICES
4. CAUTION: YBGD
PROCS ADJACENT
TO S

CATEGORY	A	B	C	D
LNAV/VNAV	2060 (488-2.8)			
LNAV	2260 (684-3.9)			
*CIRCLING	2440 (864-2.4)	2680 (1104-4.0)		NOT AUTHORISED
ALTERNATE	(1364-4.4)	(1604-6.0)		NOT APPLICABLE

EWAGN02-177