


GNSS ARRIVAL PROCEDURES MUDGE, NSW (YMDG) Page 1

04 SEP 2025

FIA BN CEN 133.05	CTAF 126.7	PAL 122.3		Bearings are Magnetic Elevations in FEET AMSL
----------------------	---------------	--------------	--	--



25 NM MSA

4100

MDG NDB


4800

B-170°

B-245°

REFERENCE WAYPOINT MDG NDB

AWIS (PHONE) 02 9353 6439



NO CIRCLING


10 NM MSA 4500


MDG
NDB 398

AD ELEV 1545

* NO CIRCLING IN SECTOR S OF RWY 04/22 AND E OF RWY 16/34.

SECTOR A






NDB


MISSED APPROACH:

TURN AS APPROPRIATE,
TRACK 150°. CLIMB TO 4800ft.

NM TO MDG NDB	25	15		7	5	3	0								
CIRCLING MINIMA				A,B: 3200-2.4		C: 3520-4.0		D: N/A							
NM TO MDG NDB	6.8	6	5	4	3	2.7	2	1.7							
ALT (3° APCH PATH)	4800	4550	4230	3920	3600	3520	3280	3200							

SECTOR B






NDB


MISSED APPROACH:

TURN RIGHT,
TRACK 300°. CLIMB TO 4100ft.

NM TO MDG NDB	25	15		8	5	3	0								
CIRCLING MINIMA				A,B: 3160-2.4		C: 3520-4.0		D: N/A							
NM TO MDG NDB	5.5	5	4	3	2	1.5	1	0.4							
ALT (3° APCH PATH)	4800	4630	4320	4000	3680	3520	3360	3160							

SECTOR C





NDB

MISSED APPROACH:

TURN AS APPROPRIATE,
TRACK 300°. CLIMB TO 4100ft.

NM TO MDG NDB	25	15		7	5	3	2	0							
CIRCLING MINIMA				A,B: 3150-2.4		C: 3520-4.0		D: N/A							
NM TO MDG NDB	5.5	5	4	3	2	1.5	1	0.3							
ALT (3° APCH PATH)	4800	4630	4320	4000	3680	3520	3360	3150							

Changes: SECTOR C MINIMA.

MDGDG01-184