

RNP Z RWY 16
MELBOURNE, VIC (YMML)

ATIS
114.1 118.0

APP
132.0

TWR
120.5

SMC
121.7

**RNP APCH
LNAV/VNAV RQMNTS:**

- YMML QNH RQ
- YMML TEMP RQ
- PROC TEMP RANGE -5°C to +60°C

Holding as directed by ATC

TR IN TURN	TIME	MIN ALT	DME LMT
/	/	/	/

ATC APCH SPEEDS

NM FM THR	SPEED KT
BELTA	185-160
5	160-150

Scale 1:500,000

AD ELEV 434

Bearings are Magnetic
Elevations in FEET AMSL

NM TO NEXT WPT	ANBEM	2	1	MMLNF	5	4	3	2	1.3	1	RW16	
ALT (3° APCH PATH)	3000	2880	2560	2240	2070	1760	1440	1120	890	810		

MISSED APPROACH:
 TRACK DCT TO MMLNH,
 THEN TRACK 160°
 CLIMB TO 4000ft OR
 AS DIRECTED BY ATC.

NM TO RW16

11.6 7.9 5.5 4 2 0 3

3000 159° 3000 3° 2100 160° 1700 160° 1100 160° TCH 50FT THR 16 ELEV 432

CATEGORY	A	B	C	D
LNAV/VNAV		810 (378-1.2)		
LNAV		890 (456-1.7)		
CIRCLING	1140 (706-2.4)		1450 (1016-4.0)	1600 (1166-5.0)
ALTERNATE	(1206-4.4)		(1516-6.0)	(1666-7.0)

Changes: WPT NAMES, Editorial.

MMLGN03-183