

RNP RWY 23
ADELAIDE, SA (YPAD)

ATIS
116.4 134.5

APP
118.2 124.2

TWR
120.5

SMC
121.7

RNP APCH
 • LNAV/VNAV RQMNTS:
 • YPAD LOCAL QNH RQ
 • YPAD LOCAL TEMP RQ
 • PROC TEMP RANGE
 -5°C TO +61°C

Holding at PADNJ

TR IN TURN TIME MIN ALT DME LMT
 292° Right 1 3800

ATC APCH SPEEDS

NM FM THR	SPEED KT
10	185-160
5	160-150

AD ELEV 20
 Bearings are Magnetic
 Elevations in FEET AMSL

NM TO NEXT WPT	PADNM	1.1	1.4	2	2.3	3	4	5	6	7	PADNF	1	2	3.7
ALT (3° APCH PATH)		430	520	710	800	1030	1340	1660	1980	2300	2620	2940	3250	3800

MISSED APPROACH:
 TRACK DCT TO PADNH, THEN TRACK 222°
 CLIMB TO 3800ft OR AS DIRECTED BY ATC.

MAHF PADNH MAPt PADNM FAF PADNF IF PADNI IAF

222° 222° 3250 3° 3800

2620 2400 3000 3800

TCH 50FT
THR 23 ELEV 20

VIRAT (14.0NM) PADNJ (18.7NM)

NM TO PADNM 5 0 2.3 8 10 12 15.7

1. MAX IAS:
INITIAL : 210KT.
- *2. NO CIRCLING SOUTH
OF RWY 05/23 BEYOND
4 DME AD OR BEYOND
3NM FM THR 05/23/30.
3. HLDG MAY NOT BE
CONTAINED IN CTA.
4. **COLOUR:** SEE
SPEC NOTICES.

CATEGORY	A	B	C	D
LNAV/VNAV		430 (410-1.5)		
LNAV		520 (500-2.0)		
CIRCLING *	900 (880-2.4)		1000 (980-4.0)	1000 (980-5.0)
ALTERNATE	(1380-4.4)		(1480-6.0)	(1480-7.0)

PADGN02-181