

RNP X RWY 29 (AR)
DARWIN, NT (YPDN)

ATIS 128.25 308 316.2

APP-E 125.2
APP-W 134.1

SMC 121.8

TWR 133.1

DEP 123.0

RNV X 29
THR ELEV 81

RNP AR APCH

- RF RQ
- YPDN ACT QNH RQ
- YPDN ACT TEMP RQ
- PROC TEMP RANGE +15°C TO +56°C

Holding at NASUX

TR	INTURN	TIME	MIN ALT	DME LMT
106°	Right	1'	3000	

NASUX

286°
17.3NM

RW29

286°
5.5NM

DN432
1800

286°
1.1NM

DN444
2100

2.6NM
286°

LAPAR
3000

2.5 NM MSA

1700

B-070° YPDN ARP B-270°

3000

10 NM MSA 3000

AD ELEV 103

Bearings are Magnetic

Elevations in FEET AMSL

CATEGORY	A	B	C	D
RNP (0.30)	N/A		DA(H) 500 (419 - 2.4) 1.5 HIALS	DA(H) 500 (419 - 2.4) 1.5 HIALS
RNP (0.15)			DA(H) 444 (363 - 2.1) 1.2 HIALS	DA(H) 444 (363 - 2.1) 1.2 HIALS
CIRCLING			NOT AUTHORISED	NOT AUTHORISED
ALTERNATE				

1. PAPI not coincident with VPA.
2. RNP 0.3 RQ FROM LAPAR TO DN432.
3. MIN MAP GRAD 4.1% TO 3000FT per ATC.

Changes: D256, D214, D213 REMOVED, Editorial.

PDNGN15-181

Prepared by GE Aerospace - ICAO Doc 9905 Compliant

© Airservices Australia

