

ILS-Z or LOC-Z RWY 18L
PEARCE, WA (YPEA)

ATIS 340 136.4 316.1
 DEP PEA CEN 123.3 135.9
 APP PEA APP 130.2
 TWR 118.3 257.8
 FIA (AH) PH CEN 135.25
 CTAF+AFRU (AH) 118.3
 AWIS (AH) 316.1

NAVAID RQ:
 • DME or GNSS (ILS)
 • DME (LOC ONLY)

Holding at SALEB

31 30 00S
 115 50 00E
 116 00 00E
 116 10 00E
 31 40 00S
 31 50 00S

2°W
 175°
 245°
 065°
 355°

0 1 2 3 4 5 NM
 Scale 1:500,000

31 30 00S
 31 40 00S
 31 50 00S

115 50 00E
 116 00 00E
 116 10 00E

25 NM MSA
 10 NM MSA 2600

2200 PEA NDB 2700
 B-180°
 B-020°

CTR BDRY
 420
 11 DME PH

175° Left
 1
 2400

* NO CIRCLING

AD ELEV 150
 Bearings are Magnetic
 Elevations in FEET AMSL

[illegible]

1. MAX IAS:
HOLDING : 210KT
- * 2. NO CIRCLING EAST
OF RWY 18L / 36R.
3. TRAINING DURING
CTAF HOURS -
REFER ERSA FAC.

CATEGORY	A	B	C	D
S-I ILS		430 (315)	1.8 (VIS 1.5 WITH ACTUAL QNH)	
S-I LOC/DME		670 (555-3.1)		
CIRCLING *	790 (640-2.4)		1010 (860-4.0)	1070 (920-5.0)
ALTERNATE	(1140-4.4)		(1360-6.0)	(1420-7.0)

PFAD01-185