


STANDARD INSTRUMENT ARRIVAL (STAR)
ATNAR TWO ECHO (RNAV)
EDINBURGH, SA (YPED)

04 SEP 2025

ATIS	AWIS (AH)	SMC / ACD	TWR	APP (AD)	CTAF+AFRU	FIA	Bearings are Magnetic
126.25 316.3	316.3	134.1	118.3 257.8	128.6 306.3	118.3	AD CEN 130.45	Elevations in FEET AMSL



ARRIVAL: ATNAR TWO ECHO

RWY 18:

- FROM ATNAR TRACK 099° to GULFS
Cross GULFS AT or BLW FL130
- Track 074° to LATUL
Cross LATUL AT or BLW 9000FT
- Track 036° to UGUXA
Cross UGUXA AT or BLW 8000FT
- Track 015° to PAVSA
Cross PAVSA AT or BLW 5000FT
- Track 015° to TUPSI
- Track 090° to APOKI
Cross APOKI AT or ABV 3300FT
- Track 180° to UPTUN
- Track via ILS-Z or LOC-Z RWY 18 or RNP RWY 18

RWY 36:

- FROM ATNAR TRACK 099° to GULFS
Cross GULFS AT or BLW FL130
- Track 074° to LATUL
Cross LATUL AT or BLW 9000FT
- Track 036° to UGUXA
Cross UGUXA AT or BLW 8000FT
- Track 015° to PAVSA
Cross PAVSA AT or BLW 5000FT
- Track 015° to TUPSI
- Track 090° to APOKI
Cross APOKI AT or ABV 3300FT
- Track 180° to UPTUN
- Track via ILS-Z or LOC-Z RWY 18 or RNP RWY 18 and make CIRCLING approach RWY 36

COMMUNICATIONS FAILURE PROCEDURE

On recognition of communication failure

- Squawk 7600, comply with vertical navigation requirements, but not below MSA.
- Track via the latest STAR clearance to the nominated runway, then fly the most suitable approach in accordance with ERSa EMERG Section 1.5.

