


PERTH/JANDAKOT, WA (YPJT)

03 SEP 2026

ATIS (AWIS AH) 128.65 281	SMC 124.3	TWR (CTAF+AFRU AH) 118.1	FIA PH CEN 135.25	APP (PH) 123.6 132.95	DEP (PH) 118.7	PAL+AA (AH) 123.9	Bearings are Magnetic Elevations in FEET AMSL
------------------------------	--------------	--------------------------------	----------------------	--------------------------	-------------------	----------------------	--



SCARP SIX DEPARTURE

PROC NOT AVBL FROM RWY 06R/24L

RWY 06L (VISUAL)

- GRAD 3.3%
- Track 056°
- After passing 600ft turn RIGHT visually to intercept and track 115° to SCARP
- From SCARP track 115°

REQUIREMENTS RWY 06L:

- GRAD 3.3%
- Minimum Cloud Base 700ft
- ACFT must remain visual within Jandakot CTR (3NM from ARP) until the end of initial turn.
- Visual segment terminated when established on track to intercept 115° to SCARP. Cross JT CTR boundary AT or ABV 700ft.

RWY 24R

- GRAD 3.3%
- Track 236°
- At passing 600ft turn LEFT to intercept and track 115° to SCARP
- From SCARP track 115°

RWY 12

- GRAD 3.3%
- Track 116°
- After passing 600ft turn LEFT to intercept and track 115° to SCARP
- From SCARP track 115°

RWY 30

- GRAD 3.3%
- Track 296°
- After passing 600ft turn LEFT to intercept and track 115° to SCARP
- From SCARP track 115°

COMMUNICATIONS FAILURE PROCEDURE

On recognition of communications failure

- Squawk 7600
- Maintain procedure track for two minutes, and
- CLIMB IF NECESSARY TO MINIMUM SAFE ALTITUDE, to maintain terrain clearance, then
- Proceed in accordance with the latest ATC route clearance acknowledged.

Changes: CHART TITLE, PROCEDURE NAMES, VALIDITY INDICATOR, INSTRUCTIONS, Editorial.

PJTDP01-188