


STANDARD INSTRUMENT ARRIVAL (STAR) JANDAKOT FOUR ROMEO ARRIVAL (RNAV) PERTH/JANDAKOT, WA (YPJT)

03 SEP 2026

ATIS (AWIS AH) 128.65 281	SMC 124.3	TWR (CTAF+AFRU AH) 118.1	FIA PH CEN 135.25	APP (PH) 123.6 132.95	DEP (PH) 118.7	PAL+AA (AH) 123.9	Bearings are Magnetic Elevations in FEET AMSL
------------------------------	--------------	--------------------------------	----------------------	--------------------------	-------------------	----------------------	--



TRANSITIONS:

**LAVEX:
(NON-JET)**

- From LAVEX, track 269° to BUVOT
- Turn RIGHT track 287° to RONAN
- Cross** RONAN AT or BLW FL110
- Track 287° to UNDOU
- Cross** UNDOU AT or BLW 7000ft
- Track 287° to ROLOB
- Then follow ARRIVAL instructions

**KABLI:
(JET)**

- From KABLI, track 310° to BOOKA
- Track 310° to DUDIN
- Cross** DUDIN AT or BLW FL110
- Turn LEFT track 303° to VEPAN
- Cross** VEPAN AT or BLW 7000ft
- Track 303° to ROLOB
- Then follow ARRIVAL instructions

JANDAKOT FOUR ROMEO ARRIVAL

- From ROLOB, turn LEFT
- Track 240° to PH VOR
- Expect radar vectors to YPJT

COMMUNICATIONS FAILURE: PROCEDURE IN IMC

- Squawk 7600
- Comply with vertical navigation requirements and maintain minimum safe altitude.
- IF UNDER PILOT NAVIGATION track via the STAR clearance to Jandakot NDB, then in accordance with ERSa, EMERG.
- IF UNDER RADAR VECTOR, maintain vector for 2 minutes, then track to the Jandakot NDB, then in accordance with ERSa, EMERG.

Changes: TRACK BEARINGS, VALIDITY INDICATOR.

PJTSR03-188