

RNP RWY 21
PERTH, WA (YPPH)

ATIS 113.7 123.8

APP 123.6 132.95

TWR 127.4

SMC E of RWY 03/21 122.2 W of RWY 03/21 121.7

ATC APCH SPEEDS			
NM	FM	THR	SPEED KT
HAIGH			185-160
5			160-150

MAX IAS 230KT

MAX IAS 185KT

PH2ND 096° 4NM

WOOFY 058° 6.9NM

PH2NM 196° 3.7NM

KOORI 303° 6.7NM

HAIGH 196° 4NM

PH2NF 196° 3.7NM

WOORA

IPMOR ARR GORMA

25 NM MSA 3000

10 NM MSA 2700

JANDAKOT CTR

YPJT 1500 SEC

Scale 1:500,000

AD ELEV 67

Bearings are Magnetic Elevations in FEET AMSL

NM TO NEXT WPT	PH2NM	0.7	1.2	2	3	PH2NF	1	2.1	3	HAIGH			
ALT (3° APCH PATH)		400	560	820	1130	1350	1660	2010	2300	2620			

MISSED APPROACH:
 TRACK 196°. AT 2000ft TURN LEFT, TRACK 170°. CLIMB TO 3000ft OR AS DIRECTED BY ATC.

MAPt PH2NM FAF PH2NF IF/IAF HAIGH IAF KOORI (14.4NM) PH2ND (11.7NM) IAF

170° 196° 170°

TCH 50ft 2000 1350 2010 196° 2620 2500 3000 3000 WOOFY

THR 21 ELEV 43

NM TO PH2NM

0.3 0 3.7 5.8 7.7 18.6

CATEGORY	A	B	C	D
LNAV/VNAV		400	(357-1.1)	
LNAV		560	(517-2.0)	
CIRCLING*	760	(693-2.4)	1440	(1373-4.0) 1440 (1373-5.0)
ALTERNATE		(1193-4.4)	(1873-6.0)	(1873-7.0)

1. MAX IAS:
HAIGH : 185KT.
WOOFY : 230KT.

* NO CIRCLING CAT C & D
ACFT BEYOND 4NM PH
E OF RWY 03/21 AND 06/24.

3. COLOUR: SEE
SPEC NOTICES.

PPHGN02-183