# STANDARD INSTRUMENT ARRIVAL (STAR) BOREE FOUR PAPA ARRIVAL (RNAV) SYDNEY/KINGSFORD SMITH, NSW (YSSY)

### 12 JUN 2025

12 0011 2020				
ATIS AF 118.55 124		TWR <b>120.5</b>	SMC E OF RWY 16R/34L <b>121.7</b> W OF RWY 16R/34L <b>126.5</b>	Bearings are Magnetic Elevations in FEET AMSL
NOT TO SCALE		BOREE \$\frac{9000}{2000}		SPEED MAX IAS 250KT BELOW 10,000ft
μ <sub>ω</sub>		VASRA → <u>8000</u>		RNP 1
PRM OPS*  DUAL VHF COMS  REQUIRED		(10)		
ATC APCH SPEEDS  NM FM TD   SPEED KT  URDEN   185 -160  5   160 -150		DALAR → 5000 4000 35,8 DUMOP → 3000		
25 NM MS <sub>4</sub> 2700 (YSSY) ARP		UR	0 MAX IAS 185KT	

#### ARRIVAL: BOREE FOUR PAPA

#### **RWY 16R:**

Cross BOREE AT or ABV 9000ft, then

- From BOREE track 158° to VASRA Cross VASRA AT or ABV 8000ft
- Turn RIGHT, track 167° to DALAR
   Cross DALAR between 4000ft and 5000ft
- Turn LEFT, track 155° to DUMOP Cross DUMOP AT 3000ft
- From DUMOP track 155° via FINAL APCH COURSE to URDEN MAX IAS 185KT from URDEN
- Track via GLS RWY 16R or ILS RWY 16R

\* PRM OPS: SEE PRM USER INST FOR ADDITIONAL REQUIREMENTS.

## COMMUNICATIONS FAILURE: PROCEDURE IN IMC IF ABLE CTC SY APP +61 2 9556 6515

- Squawk 7600, comply with vertical navigation requirements, but not below MSA.
- Track via the latest STAR clearance to the nominated runway, then fly the most suitable approach in accordance with ERSA EMERG Section 1.5.

Changes: ATIS FREQ REMOVED, Editorial.

