

RNP RWY 12
WYNDHAM, WA (YWYM)

FIA BN CEN 122.4

CTAF+AFRU 128.0

AFRU+PAL 128.0

127 50 00E

128 00 00E

128 10 00E

15 20 00S

15 30 00S

1083

YM2WE

122° 5NM

192° 5NM

YM2WD

052° 5NM

YM2WI

122° 5NM

YM2WF

122° 7NM

797

525

1575

1050

1093

570

1214

1116

853

850

508

YM2WM

3NM

YM2NH

1200

1050

320°

25 NM MSA

2400

3100

10 NM MSA 2800

Scale 1:500,000

5NM

2°E

Holding at YM2WE

232°

052°

302°

TR	TURN	TIME	MIN ALT	DME LMT
122°	Right	1	3100	

* NO CIRCLING

AD ELEV 15

Bearings are Magnetic Elevations in FEET AMSL

NM TO NEXT WPT	2	1	YM2WF	6	5	4	3	2.4	YM2WM				
ALT (3° APCH PATH)	3100	2780	2470	2150	1830	1510	1190	1010					

MISSED APPROACH:
 TRACK DCT TO YM2WH
 AT OR ABV 1200FT
 TURN LEFT
 TRACK 320°
 CLIMB TO 3100FT

IAF
 IF YM2WI
 FAF YM2WF
 MAPt YM2WM
 MAHf YM2WH

3100
 YM2WD
 YM2WE
 YM2WG

3100
 122°
 3°
 2470
 122°
 MDA
 MAPt
 320°
1200
 THR 12 ELEV 15

NM TO
 YM2WM

17 12 7 0 0.5 3

CATEGORY	A	B	C	D
LNAV	1010 (995-5.0)			NOT APPLICABLE
CIRCLING *	1450 (1435-2.4)		1630 (1615-4.0)	
ALTERNATE	(1935-4.4)		(2115-6.0)	

1. MAX IAS :
INITIAL : 210KT.
- * 2. NO CIRCLING NTH
OF RWY 12/30.
3. AWIS (PHONE)
08 6216 2642

WYMGN01-172