

**BOOLGEEDA****ELEV 1870****AVFAX CODE 6825**

WA

UTC +8

YBGD


223228S

1171610E

VAR 1 DEG E

CERT

AD OPR Hamersley Iron Pty Ltd, Level 8, 93-95 William St, Perth, WA, 6000. Email: bgdairport@amsaustralia.com. PH AD Manager 08 6213 9002, if not AVBL phone 0448 077 353.

**REMARKS**

Restricted OPS: 24HR PPR from AD OPR (AD Manager).

**HANDLING SERVICES AND FACILITIES**

VIVA Energy: VIVA Energy Australia Pty Ltd 2200-1000 UTC MON-FRI. AH call-out fee will apply, PN required. PH 0409 897 890. JET A1. VIVA Fuel2Sky Carnet card.

**APRONS AND TAXIWAYS**

TWY A - Code C, WID 18M, bitumen seal.

**AERODROME OBSTACLES**

1. Extensive terrain penetrations:
  - a. 2,943FT AMSL PSN BTN BRG 293-045 MAG 2,000-7,000M FM ARP.
  - b. 3,153FT AMSL PSN BTN BRG 075-093 MAG 12,000-16,000M FM ARP.
  - c. 2,494FT AMSL PSN BTN BRG 112-159 MAG 4,000-7,000M FM ARP.
2. Mast LIT 2,100FT AMSL PSN BRG 128 MAG 5,200M FM ARP.
3. MIOL for terrain penetrations of the COS, Inner HZS and APCH SFC:
  - a. 2,953FT AMSL BRG 018 MAG 3.19NM FM ARP 719FT ABV COS.
  - b. 2,693FT AMSL BRG 009 MAG 2.53NM FM ARP 630FT ABV COS.
  - c. 2,552FT AMSL BRG 348 MAG 2.29NM FM ARP 535FT ABV inner HZS.
  - d. 2,470FT AMSL BRG 317 MAG 2.28NM FM ARP 453FT ABV inner HZS.
  - e. 3,162FT AMSL BRG 075 MAG 7.84NM FM ARP 801FT ABV APCH SFC.
  - f. 2,687FT AMSL BRG 081 MAG 7.80NM FM ARP 325FT ABV APCH SFC.
  - g. 2,604FT AMSL BRG 090 MAG 7.48NM FM ARP 243FT ABV APCH SFC.
4. Unlit APN flood LGT:
  - a. 1,944FT AMSL BRG 095 MAG 0.61NM FM ARP. Infringes TNS by 2FT.
  - b. 1,943FT AMSL BRG 095 MAG 0.59NM FM ARP. Infringes TNS by 1FT.

**METEOROLOGICAL INFORMATION PROVIDED**

1. TAF CAT C, METAR/SPECI.
2. AWIS FREQ 122.475 - Report faults AD OPR.

**PHYSICAL CHARACTERISTICS**

08/26            084   72a   PCN 44 /F /A /1441 (209PSI) /T Sealed            WID 45    RWS 300

**AERODROME AND APPROACH LIGHTING**

RWY 08/26	LIRL	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 08/26	PAPI(1)	AFRU+PAL 126.7	3.0 DEG49FT	SDBY PWR AVBL
RWY 08/26	PTBL(2)			BY PRIOR
				ARRANGEMENT

- (1) Left side.
- (2) EMERG only, 2HR PN.

**OTHER LIGHTING**

1. SDBY PWR switchover time: 10 SEC.
2. TWY LGT: Blue edge.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA            MELBOURNE CENTRE            125.7 CCT area

**LOCAL TRAFFIC REGULATIONS**

1. All ACFT to use turning nodes, MAX radius turns at MIN speed.
2. All ACFT ABV 5,700KG MTOW must park on marked bays using appropriate lead-in lines.
3. Unlit HEL PRKG AVBL, with marked pad, 200M W of terminal building.
4. HEL to park clear of ring road to allow fuel tanker access.

**FLIGHT PROCEDURES**

Right hand CCTS only RWY 08.

**CTAF - AFRU** 126.7

**ADDITIONAL INFORMATION**

1. Open pit mine blasting within 5NM S and SW of AD SFC - 2,000FT.
2. Caution: YBGD is in close proximity to YEWA (APRX 22NM WNW of YBGD). The APCH/DEP tracks cross close to the ground.

**CHARTS RELATED TO THE AERODROME**

1. WAC 3229.
  2. Also refer to AIP Departure and Approach Procedures.
-