BENALLA **FLFV 569**


AVFAX CODE 3030

VIC

UTC +10 363315S 1460033E VAR 12 DEG E

AD OPR Benalla Rural City Council, PO Box 227, Benalla, VIC, 3672.

Email: council@benalla.vic.gov.au. PH 03 5760 2600.



REMARKS

AD Charges: All AVTUR ACFT.

HANDLING SERVICES AND FACILITIES

Aero Refuellers: H24 card swipe, AVGAS and JET A1 bowsers, Accepts Aero Refuellers cards. V and MC.

AERODROME OBSTACLES

- 30FT PWR line 365DEG 0.2NM FM RWY 17 THR. 1.
- 79FT water tower 248DEG 0.85NM FM RWY 08 THR. 2.
- 3 Unlit 100FT radio tower 272DEG 0.94NM FM RWY 08 THR.

PHYSICAL CHARACTERISTICS

34a PCN 10 /F /B /450 (65PSI) /U Sealed. **WID 18 RWS 90** 08/26 083 17/35 163 24c 5700/450 (65PSI) Grass slit clay. **WID 30 RWS 90**

AERODROME AND APPROACH LIGHTING

RWY 08/26 LIRL PAL 123.4

OTHER LIGHTING

TWY LGT: Green CL.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.2 Circuit area

FLIGHT PROCEDURES

- CONTRA CIRCUITS IN OPERATION THERE IS NO DEAD SIDE WITH CONTRA 1. CIRCUITS.
- 2. Gliders and tugs use separate glider strips 08/26 and 17/35, marked by orange gable markers. Also AVBL for tailskid equipped ACFT.
- 3. Glider/tug circuits to N or E, other ACFT circuits to S or W. Other ACFT must not infringe glider circuit BLW 2,000FT AGL. Right hand circuits RWY 08 and 17. Gliders/tugs right hand circuits glider strip RWY 26 and 35.
- Tugs towing gliders DEP glider strip 26 turn in the direction of the circuit by the earlier of 4. either the AD boundary or 200FT AGL.
- 5. WHERE POSSIBLE ACFT SHOULD CONFORM TO ESTABLISHED RWY DIRECTION IN USE. Join circuit in downwind position or upwind along RWY 08/26 or 17/35.
- If use of a crossing RWY is operationally necessary a wide circuit to join a long final clear of 6. established circuit traffic is advised. On DEP maintain RWY heading until clear of traffic.
- No provision for a straight in APCH to RWY 26 at night. 7.

CTAF 125.6

YBI A

CERT

NOISE ABATEMENT PROCEDURES

- 1. NOISE ABATEMENT: RWY 17/35 fly wide circuits to avoid overflying Benalla township.
- 2. RWY 26 maintain RWY heading to 1,000FT AGL or until beyond hospital to left of extended centre line.

ADDITIONAL INFORMATION

- CAUTION: Restricted area for Benalla explosive plant, R364 (1NM RAD of 362918S 1455935E, SFC - 2,000FT) is BTN 2.8 and 4.8NM N of AD on RCL for RWY 17/35. ACFT should be at or ABV 2,000FT (1,450FT AGL APRX) at 2.8NM N of AD.
- Manned balloon OPS may occur in 3HR following first light and 2HR preceding last light.
- 3. Animal hazard (kangaroos and birds) exist.
- All pedestrians must wear high visibility clothing when airside. Failure to do so may result in an infringement of \$200, as per Benalla Rural City Council Community Local Law 2017 Clause 9 (Council Signs).
- 5. Gliding OPS HJ. Simultaneous OPS from parallel glider strips.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3470.
- 2. Also refer to AIP Departure and Approach Procedures.