


**WEIPA****ELEV 63****AVFAX CODE 4501**

QLD 124043S 1415531E UTC +10 YBWP  
 VAR 5 DEG E CERT  
 AD OPR RTA Weipa Pty Ltd, PO Box 1027, Weipa, QLD, 4874.  
 Email: brad.fowler@riotinto.com. PH AD Manager 0458 033 934.  
 Email: weiairport@amsaustralia.com. ARO 0458 033 160 H24.

**REMARKS**

- AD Charges: Landing: Piston ACFT \$8/tonne MTOW.  
Turbine ACFT \$15/tonne MTOW. Overnight Parking: Piston ACFT \$5/tonne MTOW. Turbine ACFT \$8/tonne MTOW. All prices + GST.
- This AD is a Security Controlled Airport.

**HANDLING SERVICES AND FACILITIES**

Viva Energy Aviation - JL Aviation Fuelling Pty Ltd. JET A1 and AVGAS AVBL MON-FRI  
 0800-1800 Local. Closed SAT-SUN. PH 0428 197 873.

**AERODROME OBSTACLES**

- Transitional SFC infringed by unlit aerial 32FT AGL APRX 500M W FM ARP.
- Lit Tower:
  - 283FT AMSL APRX BRG 280MAG 3.4NM FM ARP.
  - 318FT AMSL APRX BRG 340MAG 3.8NM FM ARP.

**METEOROLOGICAL INFORMATION PROVIDED**

- TAF CAT C, METAR/SPECI.
- AWIS PH 07 3564 3745 - Report faults to BoM.
- AWIS FREQ 128.075 (requires one-second pulse to activate) - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

12/30 119 54a PCN 27 /F /B /1400 (203PSI) /T Grooved. WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

|           |         |                |             |               |
|-----------|---------|----------------|-------------|---------------|
| RWY 12/30 | LIRL    | AFRU+PAL 126.7 |             | SDBY PWR AVBL |
| RWY 12/30 | PTBL(2) |                |             | BY PRIOR      |
|           |         |                |             | ARRANGEMENT   |
| RWY 12    | PAPI(1) | AFRU+PAL 126.7 | 3.0 DEG45FT | SDBY PWR AVBL |
| RWY 30    | PAPI(1) | AFRU+PAL 126.7 | 3.0 DEG46FT | SDBY PWR AVBL |

(1) Left side.

(2) EMERG only. 2HR PN.

PAL activates all lighting.

**OTHER LIGHTING**

- SDBY PWR switchover time: 15 SEC.
- TWY LGT: Blue edge.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA BRISBANE CENTRE 122.1 On Ground

**RADIO NAVIGATION AND LANDING AIDS**

|     |    |            |           |            |                                      |     |
|-----|----|------------|-----------|------------|--------------------------------------|-----|
| DME | WP | 112.8/ 75X | 124024.8S | 1415521.4E |                                      | (2) |
| NDB | WP | 377        | 123941.9S | 1415355.7E | Range 40 (HN 40) OW 140<br>(OW HN90) | (3) |
| VOR | WP | 112.8      | 124024.8S | 1415520.9E |                                      | (1) |

(1) RESTRICTION: Bearing fluctuations (+/- 4 DEG) may occur on 089 DEG RAD beyond 40NM.

(2) Antenna ELEV 81FT.

(3) 118/1.6 to ARP. Pilot MNT.

**LOCAL TRAFFIC REGULATIONS**

1. Terminal building is locked AH. Keys can be arranged through the AD Manager.
2. Any itinerant ACFT wishing to use the RPT apron is to contact the AD Manager 48HR prior to ARR at Weipa for bay number allocation.
3. Overnight parking on the RPT apron requires 48HR prior notice to AD Manager.
4. PRKG for HEL over 2,500KG MTOW restricted to unsealed section of GA APN. Exceptions require AD Manager approval.
5. Light aircraft tie-downs not strength rated.

**CTAF - AFRU 126.7**

Except when Scherger CTR and Restricted areas active.

**ADDITIONAL INFORMATION**

1. During cyclone season tie-downs shall be used on GA apron.
2. Bird hazard may exist overhead the AD particularly late afternoon until dark.
3. Weather balloon launch APRX 2315 FM 500M W ARP. Launches may occur at other times.

**CHARTS RELATED TO THE AERODROME**

1. WAC 3112.
  2. Also refer to AIP Departure and Approach Procedures.
-