


CLONCURRY**ELEV 613****AVFAX CODE 4303**

QLD 204007S 1403016E UTC +10 YCCY
 VAR 6 DEG E CERT
 AD OPR Cloncurry Shire Council, PO Box 3, Cloncurry, QLD, 4824.
 PH 07 4742 4100. ARO 0428 181 981 (H24). AH secondary
 CTC 0408 133 580. Fax 07 4742 2888.

REMARKS

1. AD Charges apply.
2. This AD is a Security Controlled Airport.

HANDLING SERVICES AND FACILITIES

Jomera Pty Ltd: Ground handling services: Aircraft marshalling, baggage/freight, passenger handling, check-in/boarding, airline representation, aircraft refuelling and crew transfers.

PH 0429 651 149, email: operations@jomera.com.au, website: jomera.com.au.

Air BP: 0730-1700 Local MON-FRI. PN required on weekends, call-out fee applies AH and on weekends. JET A1 refueller vehicle (under and overwing) and AVGAS self-service bowser - must have a BP carnet card. PH 0429 651 149 or email: airbpconj@jomera.com.au
 IOR Aviation PTY LTD: JET A1 refueller vehicle (under and overwing). 0800-1700 Local DLY, AH call-out fee applies. PH 0429 664 680.

PASSENGER FACILITIES

PT/TX (Taxi 131 008)/ LG/RF/WC/ME (07 4742 2855, 0407 696 103)

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS Phone 07 3564 3711- Report faults to BoM.
3. AWIS FREQ 128.05 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

06/24	062	38a	5700 kg/0.73 MPa	WID 18	RWS 60
12/30	122	66a	PCN 30/F/A/1.20 MPa/T	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 12/30	LIRL	AFRU+PAL 126.7	3.0 DEG46FT	SDBY PWR AVBL
RWY 12/30	PAPI(1)	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 12/30	PTBL(2)			BY PRIOR ARRANGEMENT

- (1) Left side.
 - (2) EMERG only. 40MIN PN.
- RWY edge light spacing: 12/30: 90M.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC.
2. TWY LGT: Green CL on A; Blue edge on B.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 122.4 3500FT

RADIO NAVIGATION AND LANDING AIDS

NDB CCY 264 203956.4S 1403003.8E Range 75 (HN 75)

LOCAL TRAFFIC REGULATIONS

1. Bay 1 preferred night parking operations for Saab 340 to Fokker F100 and similar ACFT.
2. RWY 12/30 ACFT ABV 20,000KG MTOW must execute turns only at RWY THR.
3. All light ACFT APN and TWY 5,700KG limit.
4. Parking restriction on RPT APN. PN required for itinerant ACFT ABV 5,700KG.
5. RWY 12 THR turning node left hand turn only for ACFT ABV 20,000KG due pavement failure.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Bird, animal and flying fox hazard exists.

CHARTS RELATED TO THE AERODROME

1. WAC 3233.
 2. Also refer to AIP Departure and Approach Procedures.
-