

GINBATA**ELEV 1409****AVFAX CODE 6831**

WA

UTC +8

YGIA

223452S


1200208E

VAR 1 DEG E

CERT

AD OPR Roy Hill Iron Ore Pty Ltd, Roy Hill Mine, PO Box Locked Bag No. 2, West Perth, WA, 6872.

Email: rh.aerodrome@royhill.com.au. PH AD Manager 08 9154 2380. ARO 0448 175 250. Mobile 0448 194 305.

**REMARKS**

1. Restricted OPS. PPR for itinerant ACFT.
2. Terminal access by prior arrangement.

HANDLING SERVICES AND FACILITIES

Air BP: JET A1 CTC AD Manager/ARO.

AERODROME OBSTACLES

1. Terrain 1,562FT AMSL BRG 061 DEG MAG 2.5NM FM ARP. Infringes inner HZS by 7FT.
2. Lit COM TWR 1,644FT AMSL BRG 037 DEG MAG 2.06NM FM ARP. Infringes inner HZS by 81FT.
3. APN flood LGT infringe TNS at FLW LOC:
 - a. BRG 038 MAG 0.19NM FM ARP. Infringes by 2FT.
 - b. BRG 047 MAG 0.23NM FM ARP. Infringes by 2FT.

METEOROLOGICAL INFORMATION PROVIDED

AWIS FREQ 123.15 (requires three one-second pulses to activate) - report faults to AD OPR.

PHYSICAL CHARACTERISTICS

09/27 089 82a PCR 370/F/B/Y/U

WID 45 RWS 300

RWY shoulders 1.5M.

AERODROME AND APPROACH LIGHTING

RWY 09/27 LIRL(1) PAL+AA 120.05

SDBY PWR AVBL

RWY 09/27 PAPI(1) PAL+AA 120.05

3.0 DEG49FT

SDBY PWR AVBL

(1) SDBY PWR supplied by AD generators.

RWY edge light spacing: 09/27: 59.6M.

OTHER LIGHTING

1. SDBY PWR (automatically activated) switchover time: 30 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE

128.15

LOCAL TRAFFIC REGULATIONS

1. AD AVBL for OPS H24.
2. All ACFT to turn at RWY ends only, MAX RAD turns at MNM speed.

FLIGHT PROCEDURES

Right hand CCTS - RWY 09.

CTAF - AFRU 127.05

AFRU signal not heard on ground.

ADDITIONAL INFORMATION

UA (multi-rotor 7KG) OPR WI 10NM radius of 223242S 1195854E BRG 304MAG 4NM FM ARP, SFC to 1,000FT AGL. OPR will BCST on 127.05 15MIN prior to launch and at 15MIN intervals whilst airborne. OPR CTC 0419 924 011.

CHARTS RELATED TO THE AERODROME

1. WAC 3229, 3230.
 2. Also refer to AIP Departure and Approach Procedures.
-