MOUNT HOTHAM AVFAX CODE 3065


FLFV 4260

 VIC
 UTC +10
 YHOT

 370254S
 1472003E
 VAR 12 DEG E
 CERT

AD OPR MHSC Transportation Services Pty Ltd, PO Box 140, Bright, VIC, 3741. PH 03 5759 4444: AD OPS 03 5159 6777 (H24): AD OPS Fax 03 5159 6776. ARO 0418 971 778: 0416 986 288.

Website: www.mthotham.com.au.



REMARKS

- AD Charges: All ACFT.
- 2. PPR FM AD OPR for all night and non-RPT OPS, refer to website for OPR approval (PDF).
- 3. Call-out fee applies for approved night OPS.

HANDLING SERVICES AND FACILITIES

JET A1 year round, 2200-0600 UTC DLY; JUN-SEP - 4HR PN. OT 24HR PN. CTC AD OPR. Call-out fee applies weekends and PH during non-winter period. EFTPOS and credit cards only.

PASSENGER FACILITIES

June/September - PT/HC/BU/AC/LG/RF/WC. OT restricted hours.

APRONS AND TAXIWAYS

- TWY B not AVBL to ACFT ABV 5,700KG MTOW.
- 2. TWY B AVBL to ACFT with a wingspan up to and not exceeding 15M.

AERODROME OBSTACLES

- Lit mast 4,460FT, BRG 291 DEG MAG 2,873M FM RWY 29 THR, 0.4M L of RCL.
- Trees:
 - a. BRG 297 DEG MAG 2,392M FM ARP. Infringes APCH SFC by 76FT.
 - b. BRG 285 DEG MAG 1,856M FM ARP. Infringes TNS by 13FT.
 - c. BRG 287 DEG MAG 1.644M FM ARP, Infringes TNS by 21FT.
 - d. BRG 286 DEG MAG 2.520M FM ARP. Infringes TNS by 50FT.
 - e. BRG 286 DEG MAG 1.654M FM ARP, Infringes TNS by 16FT.
 - f. BRG 288 DEG MAG 1,716M FM ARP. Infringes TNS by 34FT.

METEOROLOGICAL INFORMATION PROVIDED

- 1. METAR/SPECI.
- AWIS Phone 03 8470 3217 Report faults to BoM.
- AWIS FREQ 128.05 (one-second transmit pulse to activate) Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

11/29 111 48a PCN 24 /F /C /1138 (165PSI) /T WID 30 RWS 90

AFRODROME AND APPROACH LIGHTING

ALHODHOME AND ALLHOADH EIGHTING			
RWY 11/29	LIRL(2)		SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 11/29	RTIL(2)		SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 11	PAPI(1)	3.9 DEG42FT	SDBY PWR AVBL BY PRIOR ARRANGEMENT
RWY 29	PAPI(1)	3.0 DEG41FT	SDBY PWR AVBL BY PRIOR ARRANGEMENT

- (1) Left side. PN REQ
- (2) PN REQ
- 1. RWY edge light spacing: 11/29: 56M.
- 2. From JUN to SEP the primary WDI located S RWY 11/29 will be yellow.
- 3. Main PWR supply serviced by AD generator.

OTHER LIGHTING

- Secondary PWR switchover time: 15 SEC.
- 2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.2 6500FT

LOCAL TRAFFIC REGULATIONS

All ACFT required to execute 180DEG turns at RWY end turning nodes only.

FLIGHT PROCEDURES

- 1. Right hand circuits required when OPR on RWY 29.
- 2. Pilots are requested to avoid overflying the Alpine National Park (Bogong Unit).

CTAF - AFRU 126.75

CHARTS RELATED TO THE AERODROME

- 1. WAC 3470.
- 2. Also refer to AIP Departure and Approach Procedures.