

MOUNT HOTHAM**ELEV 4260****AVFAX CODE 3065**

VIC

UTC +10

YHOT

370254S


1472003E

VAR 13 DEG E

CERT

AD OPR Mt Hotham Airport Operations Pty Ltd, PO Box 8280, Northland Centre, VIC, 3072.

ARO 0467 072 476 (H24). Fax AD OPS 03 5159 6776. Website: www.mthothamairport.com.au.

**REMARKS**

1. AD Charges: All ACFT.
2. PPR FM AD OPR for all night and non-RPT OPS, refer to website for OPR approval (PDF).
3. Call-out fee applies for approved night OPS.

HANDLING SERVICES AND FACILITIES

JET A1 year round, 2200-0600 UTC DLY; JUN-SEP - 4HR PN. OT 24HR PN. CTC AD OPR.

Call-out fee applies weekends and PH during non-winter period. EFTPOS and credit cards only.

PASSENGER FACILITIES

June/September - PT/HC/BU/AC/LG/RF/WC. OT restricted hours.

APRONS AND TAXIWAYS

1. TWY B not AVBL to ACFT ABV 5,700KG MTOW.
2. TWY B AVBL to ACFT with a wingspan up to and not exceeding 15M.

AERODROME OBSTACLES

1. Lit mast 4,460FT, BRG 291 DEG MAG 2,873M FM RWY 29 THR, 0.4M L of RCL.
2. Trees:
 - a. 4,517FT AMSL PSN 370204.70S 1471848.02E APRX BRG 297 DEG MAG 2,392M FM ARP. Infringes APCH SFC by 76FT.
 - b. 4,446FT AMSL PSN 370221.17S 1471856.06E APRX BRG 289 DEG MAG 1,936M FM ARP. Infringes APCH SFC by 54FT.
 - c. 4,409FT AMSL PSN 370228.12S 1471904.67E APRX BRG 287 DEG MAG 1,644M FM ARP. Infringes TKOF SFC by 89FT.
 - d. 4,413FT AMSL PSN 370226.12S 1471902.76E APRX BRG 288 DEG MAG 1,716M FM ARP. Infringes TKOF SFC by 88FT.
 - e. 4,454FT AMSL PSN 370226.11S 1471854.18E APRX BRG 285 DEG MAG 1,903M FM ARP. Infringes TNS by 8FT.
 - f. 4,441FT AMSL PSN 370228.42S 1471904.02E APRX BRG 286 DEG MAG 1,654M FM ARP. Infringes TNS by 16FT.

METEOROLOGICAL INFORMATION PROVIDED

1. METAR/SPECI.
2. AWIS Phone 03 8470 3217 - Report faults to BoM.
3. AWIS FREQ 128.05 (one-second transmit pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

11/29 111 48a Unrated.

WID 30 RWS 90

AERODROME AND APPROACH LIGHTING

RWY 11/29 LIRL(2)

RWY 11 PAPI(1) 3.9 DEG42FT

RWY 29 PAPI(1) 3.0 DEG41FT

SDBY PWR AVBL BY
PRIOR
ARRANGEMENT
SDBY PWR AVBL BY
PRIOR
ARRANGEMENT
SDBY PWR AVBL BY
PRIOR
ARRANGEMENT

- (1) Left side. PN REQ
- (2) PN REQ
1. RWY edge light spacing: 11/29: 56M.
2. From JUN to SEP the primary WDI located S RWY 11/29 will be yellow.
3. Main PWR supply serviced by AD generator.

OTHER LIGHTING

1. Secondary PWR switchover time: 15 SEC.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.2 6500FT

LOCAL TRAFFIC REGULATIONS

All ACFT required to execute 180DEG turns at RWY end turning nodes only.

FLIGHT PROCEDURES

1. Right hand circuits required when OPR on RWY 29.
2. Pilots are requested to avoid overflying the Alpine National Park (Bogong Unit).

CTAF - AFRU 126.75**CHARTS RELATED TO THE AERODROME**

1. WAC 3470.
 2. Also refer to AIP Departure and Approach Procedures.
-