
MOUNT HOLLAND AVFAX CODE 6315

FLFV 1462

WA UTC +8 YMHL 320630S 1194536E VAR 0 DEG W CERT

AD OPR Covalent Lithium Pty Ltd, L3, 109 St Georges Tce, Perth, WA, 6000. Email: mth.aerodrome@covalentlithium.com. PH Site Contact: 08 9230 5400. ARO or AD MGR 0437 721 944 (H24). Website: www.covalentlithium.com.



REMARKS

Restricted Operations. PPR from AD MGR/ARO.

HANDLING SERVICES AND FACILITIES

Marshalling, parking allocation and ground handling services by prior arrangement with AD MGR.

APRONS AND TAXIWAYS

TWY A - Code C, WID 23M. Apron and TWY PCN 20/F/D/Y/T Bitumen.

AERODROME OBSTACLES

- Lit tower 1,622FT AMSL BRG 51 DEG MAG 0.51NM FM ARP. Infringes inner HZS by 23FT.
- Unlit tower, 1,777FT AMSL BRG 345.7 DEG MAG 1.58NM FM ARP. Infringes inner HZS by 177FT.
- Power pole, 1,623FT AMSL BRG 279 DEG MAG 1.15NM FM ARP. Infringes inner HZS by 23FT.

PHYSICAL CHARACTERISTICS

AERODROME AND APPROACH LIGHTING

RWY 08/26 LIRL AFRU+PAL 126.4

RWY 08/26 PAPI(1) AFRU+PAL 126.4 3.0 DEG40.4FT

(1) Left side.

Backup generator power available to main aerodrome lighting system via manual transfer. Allow 5 MIN for transfer.

OTHER LIGHTING

TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.4 3500FT

LOCAL TRAFFIC REGULATIONS

- All fixed wing ACFT ABV 5,700KG must make MAX RAD turns at MNM speed at turn pads to avoid SFC damage.
- Itinerant PRKG CTC AD MGR/ARO.
- 3. All ACFT to follow APN markings.
- All jet ACFT to use idle power for movements on the APN with the exception of breakaway thrust to initiate taxi.

FLIGHT PROCEDURES

Right hand CCTS on RWY 08.

CTAF - AFRU 126.4

ADDITIONAL INFORMATION

CAUTION: Blasting occurs to the N of the AD. Dust plumes may occur following blasting. Contact ARO for more details.

CHARTS RELATED TO THE AERODROME

- 1. WAC 3462.
- 2. Also refer to AIP Departure and Approach Procedures.