

MOUNT KEITH**ELEV 1792****AVFAX CODE 6605**

WA

UTC +8

YMNE

271711S


1203317E

VAR 1 DEG E

CERT

AD OPR BHP Nickel West Pty Ltd (Mount Keith), PO Box 238, Welshpool Delivery Centre, WA, 6986. Email: mountkeithaerodrome@bhp.com. PH AD MGR 0450 031 931.

Email: joseph.buchanan@bhp.com. ARO 08 9037 8748; 0499 821 780 (H24).

**REMARKS**

1. PPR for all OPS. Email ARO.
2. AD charges: ALL ACFT.

HANDLING SERVICES AND FACILITIES

No fuel AVBL.

PASSENGER FACILITIES

LG/RF/WC

AERODROME OBSTACLES

1. Unlit terrain:
 - a. 2,024FT AMSL PSN 271517.85S 1203225.94E. Infringes HZS by 85FT.
 - b. 1,998FT AMSL PSN 271449.7S 12033.22.67E. Infringes COS by 33FT.
2. Unlit earth bund:
 - a. 1,781FT AMSL PSN 271711.33S 1203316.81E. Infringes transitional SFC by 1FT.
 - b. 1,795FT AMSL PSN 271702.37S 1203242.07E. Infringes transitional SFC by 3FT.
3. Unlit fence 1,788FT AMSL PSN 271711.31S 1203317.65E. Infringes transitional SFC by 3FT.
4. Unlit mast 2,200FT AMSL PSN 271425.16S 1203325.61E. Infringes COS by 121FT.

METEOROLOGICAL INFORMATION PROVIDED

1. METAR/SPECI.
2. AWIS FREQ 133.15 - Report faults to BHP ARO Phone: 0499 821 780.

PHYSICAL CHARACTERISTICS

11/29 113 59a PCR 210/F/A/Y/U

WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 11/29 LIRL(1)

SDBY PWR AVBL

RWY 11/29 PAPI(2)

3.0 DEG42FT

SDBY PWR AVBL

(1) HN.

(2) Left side. Activated H24.

OTHER LIGHTING

1. SDBY PWR switchover time: 15 SEC. Automatic activation.
2. TWY LGT: Blue edge.
3. TWY holding point LGT: 2 x yellow.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE

118.95 On Ground

UNICOM MOUNT KEITH UNICOM (1)

126.5

(1) AVBL during scheduled movements.

LOCAL TRAFFIC REGULATIONS

1. All ACFT performing 180 DEG turns on RWY must be at MNM speed and MAX RAD WI the RWY turning nodes.
2. ACFT must be at taxiing speed when turning into and out of TWY/RWY.
3. Q400 ACFT to use F100 lead in taxi line on APN.
4. All HN OPS use Bay 1 only.

FLIGHT PROCEDURES

Right hand CCTS required when OPR RWY 11.

CTAF - AFRU 126.5

AFRU not AVBL on ground.

ADDITIONAL INFORMATION

1. Blasting HJ:
 - a. BRG 348 DEG MAG 3.4NM FM ARP. SFC to 2,000FT AGL. CTC ARO for blasting times.
 - b. BRG 170 DEG MAG 9.1NM FM ARP. SFC to 2,000FT AGL. CTC ARO for blasting times.
2. Wildlife hazards increase following rainfall events - typically between January and June.

CHARTS RELATED TO THE AERODROME

1. WAC 3345.
 2. Also refer to AIP Departure and Approach Procedures
-