

GOVE

ELEV 205

AVFAX CODE 8009

NT

121609S

1364906E

UTC +9:30


VAR 4 DEG E

YPGV

CERT

AD OPR Nhulunbuy Corporation, PO Box 345, Nhulunbuy, NT, 0881. Email: mac@ncl.net.au. PH

AD 08 8987 1370 or 0448 863 903: H24 0428 962 606.



REMARKS

- 1. AD Charges: All ACFT.
- 2. This AD is a Security Controlled Airport.
- 3. PPR from AD OPR for all ACFT OPS ABV 55,000KG MTOW.

HANDLING SERVICES AND FACILITIES

Viva Energy Aviation: Aviation Fuel Services JET A1 2130-0730 UTC, 0488 707 803, AH by prior arrangement, call-out fee applies. Fuel2Sky Carnet cards or credit cards (V and MC). H24 AVGAS bowser.

PASSENGER FACILITIES

LG/HC/RF/WC/TX.

APRONS AND TAXIWAYS

- 1. TWY C WID 20M sealed and lit.
- 2. TWY A and B 13.7M WID sealed.
- 3. TWY E WID 18M sealed and lit.
- 4. TWY D WID 12M sealed.

METEOROLOGICAL INFORMATION PROVIDED

- 1. TAF CAT C, METAR/SPECI.
- 2. AWIS Phone 08 7922 2505 - Report faults to BoM.
- 3. AWIS FREQ 123.05 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

13/31	126	72a	PCR 210/F/A/1.15 MPa/T	WID 45	RWS 150
-------	-----	-----	------------------------	--------	---------

AERODROME AND APPROACH LIGHTING

RWY 13/31	LIRL	AFRU+PAL 127.8	SDBY PWR AVBL
RWY 13/31	PAPI(1)	AFRU+PAL 127.8	SDBY PWR AVBL

(1) Left side.

RWY edge light spacing: 13/31: 60M

OTHER LIGHTING

- 1. SDBY PWR switchover time: 20 SEC.
- 2. TWY LGT: Blue edge on C and E.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 125.0 On ground

RADIO NAVIGATION AND LANDING AIDS

DME	GV	114.1/ 88X	121554.0S	1364858.6E	(2)
NDB	GV	380	121612.8S	1364927.6E	Range 65 (HN 65) OW 110 (OW HN110) (3)
VOR	GV	114.1	121554.1S	1364859.1E	(1)

- (1) 148/0.28 to ARP
- (2) Antenna ELEV 211FT.
- (3) 275/0.36 to ARP

LOCAL TRAFFIC REGULATIONS

1. ACFT ABV 10,000KG MTOW must use turning nodes for 180DEG turns, ACFT BLW 10,000KG must use MAX RAD turns to avoid pavement damage.
2. No parking on E sealed apron without PPR FM AD OPR except for refuelling purposes.
3. No parking on W sealed apron without PPR FM AD OPR.
4. Gate codes to access airside can be obtained by contacting the ARO.

CTAF - AFRU 127.8

ADDITIONAL INFORMATION

All pilots and operators must possess and display a current Aviation Security Identification Card (ASIC) when airside.

CHARTS RELATED TO THE AERODROME

1. WAC 3110.
 2. Also refer to AIP Departure and Approach Procedures.
-