

ROMA**ELEV 1027****AVFAX CODE 4101**

QLD

UTC +10

YROM

263243S

1484630E


VAR 10 DEG E

CERT

AD OPR Maranoa Regional Council, PO Box 620, Roma, QLD, 4455. Email:

airport@maranoa.qld.gov.au. ARO 0407 730 531. Council PH 1300 007 662. Fax 07 4624 6990.

Website: www.maranoa.qld.gov.au.

**REMARKS**

1. PPR for ACFT ABV 5,700KG MTOW.
2. AD Charges: For current fees and charges refer to website.
3. This AD is a Security Controlled Airport. A valid ASIC is to be displayed at all times when airside.
4. Terminal is closed to airside access except for RPT or AD approved services. Passenger and baggage screening may be in operation.

HANDLING SERVICES AND FACILITIES

AIR BP – Scott Rodgers: 2100-0700 UTC JO: PH 07 4622 1175, Mobile 0417 958 399, Fax 07 4622 1176. AVGAS 24HR Air BP Carnet Cardswipe Bowser, JET A1 (vehicle). Cash and Air BP Carnet Card. No credit cards or cheques accepted. HJ AH call-out fee applies – cash only. Agent - IOR Aviation Pty Ltd. JET A1 (vehicle) and AVGAS 100LL (vehicle and drums), AVBL H24, 1HR PN required 2100-0600 UTC MON-FRI and 2200-0600 UTC SAT and SUN. AH call-out fee applies. IOR Mobile 0499 002 781. Payment via EFTPOS, IOR account holders or PH 1300 457 467.

PASSENGER FACILITIES

TX/PT/HC/AC/LG/WC/RF/ME.

APRONS AND TAXIWAYS

TWY limitations:

- a. TWY A ABV 5,700KG MTOW;
- b. TWY B BLW 5,700KG MTOW.

AERODROME OBSTACLES

TWR LIOL:

- a. 1,407FT AMSL BRG 103 DEG MAG 4.4NM FM ARP.
- b. 1,318FT AMSL BRG 091 DEG MAG 3.5NM FM ARP.
- c. 1,138FT AMSL BRG 163 DEG MAG 1.65NM FM ARP.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS Phone 07 3564 3735 - Report faults to BoM.
3. AWIS FREQ 122.125 (requires one-second pulse to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

09/27	092	26c	Unrated. Grassed black clay	WID 18	RWS 80
18/36	182	49a	PCR 199/F/D/0.97 MPa/T	WID 30	RWS 150

AERODROME AND APPROACH LIGHTING

RWY 18/36	LIRL	AFRU+PAL 126.95		SDBY PWR AVBL
RWY 18/36	PAPI(1)	AFRU+PAL 126.95	3.0 DEG49FT	
RWY 18/36	PTBL			BY PRIOR ARRANGEMENT

- (1) Left side.
1. RWY 18/36 AGL light spacing: 90M.
 2. PAL activates all lighting.
 3. During HJ, PAL will activate PAPI only. RWY LGT will only OPR during HJ when poor light levels exist.

OTHER LIGHTING

1. TWY A LGT: Blue edge.
2. Bay 1 unlit.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 126.0 On Ground

RADIO NAVIGATION AND LANDING AIDS

NDB ROM 377 263235.1S 1484654.1E Range 90 (HN 70)

LOCAL TRAFFIC REGULATIONS

1. RWY 18/36: All ACFT ABV 5,700KG must roll through and use MAX radius turns on the RWY end turning nodes.
2. Bays 2 and 3 are Security Restricted Areas, PRKG restrictions apply during screening OPS.
3. HEL APN N of GA for LifeFlight use only.

CTAF - AFRU 126.95

ADDITIONAL INFORMATION

Bird hazard may exist - species specific NOTAM will be raised during periods of increased activity.

CHARTS RELATED TO THE AERODROME

1. WAC 3340, 3341.
 2. Also refer to AIP Departure and Approach Procedures.
-