

SHEPPARTON

AVFAX CODE 3055

ELEV 375

VIC

362544S

1452333E

UTC +10

VAR 12 DEG E

YSHT

CERT

AD OPR Greater Shepparton City Council, Locked Bag 1000, Shepparton,
VIC, 3632. ARO BH 03 5832 9700. ARO H24 0409 807 065. Fax 03 5821 6901.

- 81

Displaced THR
Refer EBSA-408

360° 3.0NM
Shepparton

1298

36

434

60

12

11

10

9

8

7

6

5

4

3

2

1

A

B

C

D

E

F

REMARKS

1. AD AVBL to ACFT ABV 5,700KG MTOW by arrangement.

2. Landing fees apply.
- HANDLING SERVICES AND FACILITIES

Gawne Aviation: 2200-0700 UTC DLY, AH PN during BH, PH 03 5823 1481.
H24 World Fuel Services AVGAS bowser WFS carnet card and credit card
(via smartphone APP) PH 0428 946 172.
- PASSENGER FACILITIES

PT/TX/HC/AC/LG/RF/WC.
- AERODROME OBSTACLES
1. Lit TWR:

a. 629FT AMSL (255FT AGL) 2.91NM N of ARP (PSN 362249.69S 1452400.91E).

b. 507FT AMSL (137.1FT AGL) 1,195M NW of ARP (PSN 362512.23S 1452305.44E).

2. Mast

a. Lit 665FT AMSL (285FT AGL) 6.37NM N of ARP (PSN 362053.24S 1452216.69E).

b. Unlit 834FT AMSL (434FT AGL) 7.66NM NE of ARP (PSN 362243.84S 1453214.57E).

3. Tree

a. 75FT AGL BRG 170 MAG 980M FM TKOF RWY 36. Infringes TNS by 7FT.

b. 70FT AGL BRG 350 MAG 1,000M FM ARP. Infringes TNS by 4FT.

4. RWY 18/36 transitional SFC infringed by tree growth on the E side of RWY (PSN 362519.67S 1452341.19E).
- METEOROLOGICAL INFORMATION PROVIDED
1. TAF CAT D, METAR/SPECI.

2. AWIS Phone 03 8470 3219 - Report faults to BoM.

3. AWIS FREQ 212 - Report faults to AD OPR.
- PHYSICAL CHARACTERISTICS
- | | | | | | |
|-------|-----|-----|---------------------------------|--------|--------|
| 09/27 | 088 | 14c | 5700 kg/0.35 MPa Brown gravel | WID 30 | RWS 90 |
| 18/36 | 179 | 43a | 5700 kg/0.45 MPa Sealed Surface | WID 18 | RWS 90 |
- AERODROME AND APPROACH LIGHTING
- | | | | |
|-----------|---------|--------------------------------------|----------------------|
| RWY 18/36 | LIRL | PAL 123.9 AFRU+PAL 118.8 | |
| RWY 18/36 | PTBL(1) | | BY PRIOR ARRANGEMENT |
| RWY 18 | PAPI | PAL 123.9 AFRU+PAL 3.0 DEG38FT 118.8 | |
| RWY 36 | PAPI | PAL 123.9 AFRU+PAL 3.3 DEG44FT 118.8 | |
- (1) EMERG use only - 45 MIN PN required

RWY edge light spacing: 18/36: 90M.
- OTHER LIGHTING
- TWY LGT: Blue edge.
- ATS AND AERODROME COMMUNICATION FACILITIES
- FIA

MELBOURNE CENTRE

122.4 Circuit Area

UNICOM

SHEPPARTON UNICOM

118.8 (1)

(1)

2200-0700 UTC DLY.
- Information may be continued on the next page: PTO

RADIO NAVIGATION AND LANDING AIDS

NDB SHT 212 362542.1S 1452345.7E Range 30 (HN 30) (1)
(1) Pilot monitored - Privately operated.

LOCAL TRAFFIC REGULATIONS

1. 15M wingspan limitation applies to TWY A, B, E and F and Taxilane A.
2. Pilots are to exercise caution while taxiing near parked ACFT.
3. RWY end sealed area north of RWY 36 for ACFT turning only HJ.

CTAF - AFRU 118.8

NOISE ABATEMENT PROCEDURES

1. Circuit training not permitted BTN 1300-2000 UTC DLY.
2. Practice instrument approaches not permitted below 1,400FT AMSL BTN 1000-2000 UTC DLY.
3. ACFT conducting practice instrument approaches in VMC using RWY 18 must break off the approach and join a normal circuit at 1,400FT AMSL.

CHARTS RELATED TO THE AERODROME

1. WAC 3469, 3470.
 2. Also refer to AIP Departure and Approach Procedures.
-