TREPELL

ELEV 891

AVFAX CODE 4319



QLD UTC +10 YTEE
215006S 1405317E VAR 6 DEG E CERT
AD OPR South32 Cannington, PO Box 5874, Townsville, QLD, 4810. PH AD Manager 0404 795 855 or 07 4747 4300. ARO on Duty 0439 760 954.

REMARKS

Restricted OPS. PPR for all OPS.

AERODROME OBSTACLES

Lit mast 1,208FT AMSL, bearing 074DEG M, 0.7NM from ARP.

METEOROLOGICAL INFORMATION PROVIDED

1. TAF CAT C, METAR/SPECI.
2. AWIS PH 07 3564 3744 - Report faults to BoM.
3. AWIS FREQ 135.55 - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

14/32 138 59a Unrated. WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 14/32	LIRL		SDBY PWR AVBL
RWY 14/32	PTBL(2)		BY PRIOR ARRANGEMENT
RWY 14	PAPI(1)	3.0 DEG46FT	SDBY PWR AVBL
RWY 32	PAPI(1)	3.0 DEG54FT	SDBY PWR AVBL

(1) Left side only
(2) EMERG only. 90MIN PN.
RWY edge light spacing: 14/32: 60M.

OTHER LIGHTING

1. SDBY PWR switchover time requires 1 HR PN - CTC ARO.
2. TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA BRISBANE CENTRE 123.95 3500FT

LOCAL TRAFFIC REGULATIONS

MAX radius turns required for ACFT on RWY 14/32 THR.

FLIGHT PROCEDURES

1. Right hand circuits required for RWY 14.
2. All pilots are required to BCST their intentions inbound on company FREQ 126.4.
3. All pilots without PPR are required to refrain FM overflying the mine site.

CTAF - AFRU 126.7

CHARTS RELATED TO THE AERODROME

1. WAC 3233.
2. Also refer to AIP Departure and Approach Procedures.

Information may be continued on the next page: PTO