


**THE GRANITES****ELEV 1299****AVFAX CODE 8402**

NT  
203254S 1302100E UTC +9:30 YTGT  
VAR 3 DEG E CERT  
AD OPR Newmont Tanami Pty Ltd, PO Box 8020, Alice Springs, NT,  
0871. Email: gts.airport@newmont.com.  
PH AD Manager 0407 953 412. ARO 0407 817 493 (H24).

**REMARKS**

PPR from AD OPR 24HR before intended OPS. Phone AD OPR.

**HANDLING SERVICES AND FACILITIES**

ACFT marshalling is provided for all ACFT ABV 5,700KG MTOW.

**AERODROME OBSTACLES**

- Lit masts:
  - 225FT ABV ARP, BRG 292 DEG MAG 4,918M FM SOT RWY 29, infringes HZS by 84FT.
  - 169FT ABV ARP, BRG 274 DEG MAG 3,524M FM ARP, infringes HZS by 31FT.
- Trees on RWS flyover.
- RWY 11/29 transition infringement trees 400M E of RWY 11 THR 75M S of RCL infringes TNS by 41FT.
- Crane 226FT AGL BRG 276 DEG MAG 1.9NM FM ARP, infringes inner HZS by 92FT.

**METEOROLOGICAL INFORMATION PROVIDED**

- TAF CAT C, METAR/SPECI.
- AWIS FREQ 133.05 (requires three one-second pulses to activate) - Report faults to AD OPR.
- AWIS PH 08 8993 8382 - Report faults to AD OPR.

**PHYSICAL CHARACTERISTICS**

11/29 114 77a PCR 224/F/A/1.08 MPa/U Sealed WID 30 RWS 150

**AERODROME AND APPROACH LIGHTING**

RWY 11/29 LIRL PAL+AA 126.7  
RWY 11/29 PAPI(1) PAL+AA 126.7 3.0 DEG52FT  
RWY 11/29 PTBL(2)

BY PRIOR  
ARRANGEMENT

- Left side.
- EMERG only. 2HR PN.
  - PAL activates AD LGT for 30 MIN.
  - RWY 11/29 edge light spacing: 60M.

**OTHER LIGHTING**

TWY LGT: Blue edge.

**ATS AND AERODROME COMMUNICATION FACILITIES**

FIA BRISBANE CENTRE 118.9

**LOCAL TRAFFIC REGULATIONS**

- All ACFT to track on RWY CL and turn on turning nodes only.
- All turns to be MAX RAD and MNM speed to avoid SFC damage.
- All jet ACFT to use idle power for movements on the APN with the exception of brakeaway thrust to initiate taxi.

**FLIGHT PROCEDURES**

Right hand circuits required when OPR on RWY 29.

**CTAF - AFRU** 126.7

**CHARTS RELATED TO THE AERODROME**

1. WAC 3231.
  2. Also refer to AIP Departure and Approach Procedure.
-