


TROPICANA
AVFAX CODE 6403
WA
291112S
AD OPR Anglogold Ashanti Australia Ltd - GPO Box B91, Perth, WA, 6838. PH 08 9265 2000: AD Manager 08 9265 2300, 08 9265 2345. ARO 08 9265 2321, 0409 310 718.

ELEV 1104
UTC +8
VAR 2 DEG E
YTRA
CERT



REMARKS

- Restricted OPS. PPR from AD OPR.
- PRI source of PWR is derived from a generator.

HANDLING SERVICES AND FACILITIES

JET A1 private installation. AVBL to routine, scheduled and emergency service flights only.

APRONS AND TAXIWAYS

TWY A: PCN 25, sealed, WID 15M.

AERODROME OBSTACLES

- Lit mast 1,464FT BRG 230DEG 4,414M FM ARP.
- Lit weather station tower 33FT AGL PSN 291113.00S 1243301.00E 105M south of RWY centre line infringes transitional SFC.

METEOROLOGICAL INFORMATION PROVIDED

- TAF CAT C, METAR/SPECI.
- AWIS PH 08 6216 2639 - Report faults to BoM.
- AWIS FREQ 133.0 - (requires three one-second pulses to activate) - Report faults to AD OPR.

PHYSICAL CHARACTERISTICS

09/27 087 69a PCN 25/F/A/1.00 MPa/U WID 30 RWS 150

AERODROME AND APPROACH LIGHTING

RWY 09/27	LIRL	AFRU+PAL 126.7		SDBY PWR AVBL
RWY 09/27	PAPI(1)	AFRU+PAL 126.7	3.0 DEG41.3FT	SDBY PWR AVBL
RWY 09/27	PTBL(2)			BY PRIOR
				ARRANGEMENT

(1) Left side.
(2) EMERG only. 90MIN PN.
RWY edge light spacing: 09/27: 60M.

OTHER LIGHTING

- SDBY PWR switchover time: 15 SEC.
- TWY LGT: Blue edge.

ATS AND AERODROME COMMUNICATION FACILITIES

FIA MELBOURNE CENTRE 125.75

LOCAL TRAFFIC REGULATIONS

- All ACFT ABV 5,700KG must use turning nodes for 180DEG turns.
- All ACFT to make MAX RAD turns at MNM speed to avoid SFC damage.

FLIGHT PROCEDURES

Right hand CCTS RWY 27.

CTAF - AFRU 126.7

ADDITIONAL INFORMATION

Potential blasting at 1300 or 1800 WST at mine site 3.8NM south of AD.

CHARTS RELATED TO THE AERODROME

1. WAC 3352.
 2. Also refer to AIP Departure and Approach Procedures.
-