

OAKEY

RWY	(CN)	TORA	TODA	ASDA	LDA
05	(MIL)	914 (2999)	974 (3195) (2.7%)	914 (2999)	914 (2999)
23	(MIL)	914 (2999)	974 (3195) (1.36%)	914 (2999)	914 (2999)
		1. TKOF/Climb SFC overall length 2,500M.			
		2. TKOF/Climb SFC inner edge WID 80M.			
		Slope 0.19% down to SW. RWY WID 23 RWS WID 90			
09	(MIL)	1089 (3573)	1149 (3770) (1.45%)	1089 (3573)	1089 (3573)
27	(MIL)	1089 (3573)	1149 (3770) (5.99%)	1089 (3573)	1089 (3573)
		1. TKOF/Climb SFC overall length 2,500M.			
		2. TKOF/Climb SFC inner edge WID 80M.			
		Slope 0.24% down to W. RWY WID 23 RWS WID 90			
14	(MIL)	1649 (5410)	1709 (5607) (2.88%)	1649 (5410)	1649 (5410)
		1. RWY 14 2% SUPP GRAD - 1637(5370)			
		2. RWY 14 5400 FT (H24).			
32	(MIL)	1707 (5600)	1767 (5797) (1.5%)	1707 (5600)	1707 (5600)
		1. RWY 32 reduced to 5,400FT (HN).			
		2. TKOF/Climb SFC inner edge WID 180.			
		3. Extra pavement 58M included in AVBL RWY 32 TORA.			
		4. TKOF/climb SFC overall length 15,000M.			
		Slope 0.03% down to NW. RWY WID 30 RWS WID 90			

SUPPLEMENTARY TAKEOFF DISTANCES

RWY05-	832(2730)(2.2)	925(3035)(2.5)			
RWY27-	908(2979)(1.9)	949(3113)(2.0)	1032(3386)(2.2)	1065(3494)(2.5)	1097(3599)(3.3)
	1136(3727)(5.0)				
RWY14-	1214(3983)(1.9)	1641(5384)(2.0)	1660(5446)(2.2)	1685(5528)(2.5)	